

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P840292

Luminaire Tested: **LDS4C08D010 EU4089035 4LBPSSQMB**

Issue Date: 8/24/2022

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



**Test Information**

Test Method: LM-79-08  
Report Number: P840292  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-18)  
Test Lab: INNOVATION CENTER  
Issue Date: 8/24/2022  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LDS4C08D010 EU4089035 4LBPSSQMB  
Description: 4 INCH 800 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, 90CRI LEDS AND 4LBPSSQ TRIM WITH MB FINISH  
Light Source: -  
Ballast/Driver: -

Luminaire Equipment: Sample No.   Condition   Description

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 700.0 lumens  
Efficiency: N/A  
Efficacy: 70.7 lumens/watt  
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.25  
Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')  
CIE Type: Direct

Input Watts (W): 9.9  
Input Voltage (V):  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P840292

CATALOG NUMBER: LDS4C08D010 EU4089035 4LBPSSQMB

### Luminous Intensity Polar Plot





TEST NUMBER: P840292

CATALOG NUMBER: LDS4C08D010 EU4089035 4LBPSSQMB

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |   |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|---|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |     | 20  |     |     |     | 20  |     |    |    |   |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |     | 30  |     |     |     | 10  |     |    | 0  |   |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30 | 10 | 0 |
| RCR |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |   |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |    |    |   |
| 1   | 112 | 108 | 105 | 102 | 109 | 106 | 103 | 100 | 102 | 99  | 97  | 98  | 96  | 94  | 94  | 93  | 92  | 90  |    |    |   |
| 2   | 104 | 97  | 92  | 88  | 101 | 96  | 91  | 87  | 92  | 88  | 85  | 89  | 86  | 83  | 86  | 83  | 81  | 79  |    |    |   |
| 3   | 96  | 88  | 81  | 76  | 94  | 86  | 80  | 75  | 83  | 78  | 74  | 81  | 76  | 73  | 78  | 75  | 72  | 70  |    |    |   |
| 4   | 89  | 79  | 72  | 66  | 87  | 78  | 71  | 66  | 76  | 70  | 65  | 73  | 68  | 64  | 71  | 67  | 63  | 62  |    |    |   |
| 5   | 83  | 72  | 64  | 59  | 81  | 71  | 64  | 58  | 69  | 63  | 58  | 67  | 61  | 57  | 65  | 60  | 57  | 55  |    |    |   |
| 6   | 77  | 66  | 58  | 52  | 75  | 65  | 57  | 52  | 63  | 56  | 52  | 61  | 56  | 51  | 60  | 55  | 51  | 49  |    |    |   |
| 7   | 72  | 60  | 52  | 47  | 70  | 59  | 52  | 47  | 58  | 51  | 46  | 56  | 50  | 46  | 55  | 50  | 46  | 44  |    |    |   |
| 8   | 67  | 55  | 47  | 42  | 66  | 54  | 47  | 42  | 53  | 47  | 42  | 52  | 46  | 42  | 51  | 46  | 41  | 40  |    |    |   |
| 9   | 63  | 51  | 43  | 38  | 62  | 50  | 43  | 38  | 49  | 43  | 38  | 48  | 42  | 38  | 47  | 42  | 38  | 36  |    |    |   |
| 10  | 59  | 47  | 40  | 35  | 58  | 47  | 40  | 35  | 46  | 39  | 35  | 45  | 39  | 35  | 44  | 39  | 35  | 33  |    |    |   |

**AVERAGE LUMINANCE (cd/sqm):**

|     |       |
|-----|-------|
|     | 0°    |
| 0°  | 35469 |
| 5°  | 35343 |
| 10° | 34958 |
| 15° | 34353 |
| 20° | 33587 |
| 25° | 32684 |
| 30° | 31653 |
| 35° | 30437 |
| 40° | 28907 |
| 45° | 26281 |
| 50° | 21691 |
| 55° | 15981 |
| 60° | 10845 |
| 65° | 6347  |
| 70° | 2511  |
| 75° | 559   |
| 80° | 722   |
| 85° | 1218  |



TEST NUMBER: P840292

CATALOG NUMBER: LDS4C08D010 EU4089035 4LBPSSQMB

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 34.6   | 4.9       |
| 10°-20°   | 96.8   | 13.8      |
| 20°-30°   | 141.2  | 20.2      |
| 30°-40°   | 161.2  | 23.0      |
| 40°-50°   | 146.6  | 20.9      |
| 50°-60°   | 86.5   | 12.4      |
| 60°-70°   | 29.0   | 4.1       |
| 70°-80°   | 3.0    | 0.4       |
| 80°-90°   | 1.0    | 0.1       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 272.7  | 39.0      |
| 0°-40°    | 433.9  | 62.0      |
| 0°-60°    | 666.9  | 95.3      |
| 0°-90°    | 700.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 700.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 368 |      |
| 5°  | 365 | 35   |
| 15° | 344 | 97   |
| 25° | 307 | 141  |
| 35° | 258 | 161  |
| 45° | 193 | 147  |
| 55° | 95  | 86   |
| 65° | 28  | 29   |
| 75° | 2   | 3    |
| 85° | 1   | 1    |
| 90° | 0   |      |



TEST NUMBER: P840292

CATALOG NUMBER: LDS4C08D010 EU4089035 4LBPSSQMB

**CANDELA DISTRIBUTION (FULL):**

|       | 0°    |
|-------|-------|
| 0°    | 367.6 |
| 2.5°  | 367.0 |
| 5°    | 364.9 |
| 7.5°  | 361.5 |
| 10°   | 356.8 |
| 12.5° | 350.7 |
| 15°   | 343.9 |
| 17.5° | 336.0 |
| 20°   | 327.1 |
| 22.5° | 317.4 |
| 25°   | 307.0 |
| 27.5° | 295.7 |
| 30°   | 284.1 |
| 32.5° | 271.5 |
| 35°   | 258.4 |
| 37.5° | 244.2 |
| 40°   | 229.5 |
| 42.5° | 212.2 |
| 45°   | 192.6 |
| 47.5° | 169.9 |
| 50°   | 144.5 |
| 52.5° | 119.2 |
| 55°   | 95.0  |
| 57.5° | 74.3  |
| 60°   | 56.2  |
| 62.5° | 40.7  |
| 65°   | 27.8  |
| 67.5° | 17.0  |
| 70°   | 8.9   |
| 72.5° | 3.4   |
| 75°   | 1.5   |
| 77.5° | 1.5   |
| 80°   | 1.3   |
| 82.5° | 1.1   |
| 85°   | 1.1   |
| 87.5° | 0.9   |
| 90°   | 0.0   |



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)