

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P840334

Luminaire Tested: **LDS4C20D010 EU4209040 4LBPSSQMB**

Issue Date: 8/24/2022

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



Test Information

Test Method: LM-79-08
Report Number: P840334
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-18)
Test Lab: INNOVATION CENTER
Issue Date: 8/24/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDS4C20D010 EU4209040 4LBPSSQMB
Description: 4 INCH 2000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS
AND 4LBPSSQ TRIM WITH MB FINISH
Light Source: -
Ballast/Driver: -

Luminaire Equipment: Sample No. Condition Description

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1588.0 lumens
Efficiency: N/A
Efficacy: 72.8 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.25
Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 21.8
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P840334

CATALOG NUMBER: LDS4C20D010 EU4209040 4LBPSSQMB

Luminous Intensity Polar Plot





TEST NUMBER: P840334

CATALOG NUMBER: LDS4C20D010 EU4209040 4LBPSSQMB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90			90
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79			79
3	96	88	81	76	94	86	80	75	83	78	74	81	76	73	78	75	72	70			70
4	89	79	72	66	87	78	71	66	76	70	65	73	68	64	71	67	63	62			62
5	83	72	64	59	81	71	64	58	69	63	58	67	61	57	65	60	57	55			55
6	77	65	58	52	75	65	57	52	63	56	52	61	56	51	60	55	51	49			49
7	72	60	52	47	70	59	52	47	58	51	46	56	50	46	55	50	46	44			44
8	67	55	47	42	66	54	47	42	53	47	42	52	46	42	51	46	41	40			40
9	63	51	43	38	62	50	43	38	49	43	38	48	42	38	47	42	38	36			36
10	59	47	40	35	58	47	40	35	46	39	35	45	39	35	44	39	35	33			33

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	80452
5°	80179
10°	79303
15°	77936
20°	76190
25°	74152
30°	71819
35°	69049
40°	65573
45°	59618
50°	49221
55°	36235
60°	24605
65°	14406
70°	5699
75°	1268
80°	1667
85°	2878



TEST NUMBER: P840334

CATALOG NUMBER: LDS4C20D010 EU4209040 4LBPSSQMB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	78.4	4.9
10°-20°	219.7	13.8
20°-30°	320.4	20.2
30°-40°	365.8	23.0
40°-50°	332.5	20.9
50°-60°	196.1	12.4
60°-70°	65.8	4.1
70°-80°	6.8	0.4
80°-90°	2.4	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	618.6	39.0
0°-40°	984.3	62.0
0°-60°	1513.0	95.3
0°-90°	1588.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1588.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	834	
5°	828	78
15°	780	220
25°	696	320
35°	586	366
45°	437	333
55°	215	196
65°	63	66
75°	3	7
85°	3	2
90°	0	



TEST NUMBER: P840334

CATALOG NUMBER: LDS4C20D010 EU4209040 4LBPSSQMB

CANDELA DISTRIBUTION (FULL):

	0°
0°	833.8
2.5°	832.5
5°	827.8
7.5°	820.1
10°	809.4
12.5°	795.6
15°	780.2
17.5°	762.2
20°	742.0
22.5°	720.1
25°	696.5
27.5°	670.8
30°	644.6
32.5°	615.8
35°	586.2
37.5°	554.0
40°	520.6
42.5°	481.5
45°	436.9
47.5°	385.4
50°	327.9
52.5°	270.4
55°	215.4
57.5°	168.7
60°	127.5
62.5°	92.3
65°	63.1
67.5°	38.6
70°	20.2
72.5°	7.7
75°	3.4
77.5°	3.4
80°	3.0
82.5°	2.6
85°	2.6
87.5°	2.1
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)