

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P777646

Luminaire Tested: LERS4D08D010-EC4DR200210IC9040-4LBS1LI

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P777646
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2310-195-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LERS4D08D010-EC4DR200210IC9040-4LBS1LI
Description: 4 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 20° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 949.8 lumens
Efficiency: N/A
Efficacy: 106.7 lumens/watt
Spacing Criteria (0/90/45): 0.34 / 0.34 / 0.36
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 8.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P777646

CATALOG NUMBER: LERS4D08D010-EC4DR200210IC9040-4LBS1LI

Luminous Intensity Polar Plot





TEST NUMBER: P777646

CATALOG NUMBER: LERS4D08D010-EC4DR200210IC9040-4LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20																	
RC	80									50									30									10									0								
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0															
RCR																																													
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																											
1	115	113	111	109	113	111	109	108	107	106	104	103	102	101	100	99	98	97	98	96	95	94	94	92	91	91	89	88	85																
2	111	108	105	102	109	106	104	101	103	101	99	100	99	97	98	96	95	94	94	92	91	91	89	88	85																				
3	108	103	100	97	106	102	99	96	100	97	95	97	95	93	95	93	92	91	91	89	88	85																							
4	105	99	96	93	103	98	95	92	96	93	91	95	92	90	93	91	89	88	85																										
5	102	96	92	89	100	95	91	89	94	90	88	92	89	87	91	88	86	85																											
6	99	93	89	86	98	92	88	86	91	87	85	90	87	84	88	86	84	83																											
7	96	90	86	83	95	89	86	83	88	85	82	87	84	82	86	84	82	81																											
8	94	87	83	81	93	87	83	80	86	83	80	85	82	80	84	82	80	79																											
9	91	85	81	78	91	85	81	78	84	80	78	83	80	78	82	80	78	77																											
10	89	83	79	76	88	82	79	76	82	78	76	81	78	76	81	78	76	75																											

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	590685
5°	532904
10°	299100
15°	152038
20°	64369
25°	29717
30°	15733
35°	8470
40°	4536
45°	2673
50°	1547
55°	819
60°	524
65°	362
70°	160
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 2673 cd/sqm



TEST NUMBER: P777646

CATALOG NUMBER: LERS4D08D010-EC4DR200210IC9040-4LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	384.9	40.5
10°-20°	379.0	39.9
20°-30°	123.8	13.0
30°-40°	42.1	4.4
40°-50°	14.2	1.5
50°-60°	4.3	0.4
60°-70°	1.4	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	887.7	93.5
0°-40°	929.9	97.9
0°-60°	948.3	99.8
0°-90°	949.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	949.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5406	
5°	4859	385
15°	1344	379
25°	246	124
35°	64	42
45°	17	14
55°	4	4
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P777646

CATALOG NUMBER: LERS4D08D010-EC4DR200210IC9040-4LBS1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	5406.2
0.5°	5406.2
1°	5399.4
1.5°	5386.0
2°	5361.4
2.5°	5328.7
3°	5282.5
3.5°	5218.0
4°	5122.2
4.5°	5005.7
5°	4858.8
5.5°	4665.8
6°	4467.9
6.5°	4241.2
7°	4019.3
7.5°	3759.3
8°	3527.3
8.5°	3293.8
9°	3078.1
9.5°	2880.3
10°	2695.9
12.5°	1935.7
15°	1344.1
17.5°	878.1
20°	553.6
22.5°	358.6
25°	246.5
27.5°	173.3
30°	124.7
32.5°	89.5
35°	63.5
37.5°	44.3
40°	31.8
42.5°	23.1
45°	17.3
47.5°	13.5
50°	9.1
52.5°	5.8
55°	4.3
57.5°	3.4
60°	2.4
62.5°	1.9
65°	1.4



TEST NUMBER: P777646

CATALOG NUMBER: LERS4D08D010-EC4DR200210IC9040-4LBS1LI

CANDELA DISTRIBUTION (continued):

	0°
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report





— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



67.5°		1.0
70°		0.5

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)