

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P210690

Luminaire Tested: **LE_4B10D010 EC4B10209024 4LBM1GPH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P210690
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B10D010 EC4B10209024 4LBM1GPH
Description: PORTFOLIO 4 INCH CYLINDER
MEDIUM DISTRIBUTION WITH GRAPHITE HAZE TRIM
WATTAGE D010TR-10.05W DE010-10.58W D5LT-10.2W DMX-10.6W DL2-11.8W
DL3-11.1W DLE-11.39W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 485.8 lumens
Efficiency: N/A
Efficacy: 49.1 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.92
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P210690

CATALOG NUMBER: LE_4B10D010 EC4B10209024 4LBM1GPH

Luminous Intensity Polar Plot





TEST NUMBER: P210690

CATALOG NUMBER: LE_4B10D010 EC4B10209024 4LBM1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	101		100	99	98		97
2	107	102	98	94	105	100	97	93	97	94	91		94	92	89		91
3	102	95	90	85	100	93	89	85	91	87	83		88	85	82		86
4	96	88	82	78	94	87	82	78	85	80	77		83	79	76		81
5	91	82	76	72	89	81	76	71	79	74	71		78	73	70		76
6	86	77	71	66	85	76	70	66	74	69	65		73	68	65		72
7	82	72	66	61	80	71	65	61	70	65	61		69	64	60		68
8	77	67	61	57	76	67	61	57	66	60	57		65	60	56		64
9	73	63	57	53	72	63	57	53	62	57	53		61	56	53		60
10	70	60	54	50	69	59	54	50	59	53	50		58	53	49		57

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P210690

CATALOG NUMBER: LE_4B10D010 EC4B10209024 4LBM1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	46.0	9.5
10°-20°	119.8	24.7
20°-30°	153.7	31.6
30°-40°	111.1	22.9
40°-50°	39.9	8.2
50°-60°	10.7	2.2
60°-70°	3.5	0.7
70°-80°	1.1	0.2
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	319.5	65.8
0°-40°	430.6	88.6
0°-60°	481.2	99.1
0°-90°	485.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	485.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	499	
5°	490	46
15°	427	120
25°	339	154
35°	178	111
45°	48	40
55°	11	11
65°	3	4
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P210690

CATALOG NUMBER: LE_4B10D010 EC4B10209024 4LBM1GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	499.4
2.5°	497.3
5°	490.2
7.5°	479.0
10°	463.7
12.5°	446.3
15°	426.9
17.5°	407.4
20°	388.0
22.5°	365.6
25°	339.1
27.5°	308.4
30°	269.6
32.5°	224.7
35°	177.7
37.5°	134.8
40°	98.0
42.5°	69.5
45°	48.0
47.5°	32.7
50°	21.5
52.5°	15.3
55°	11.3
57.5°	8.1
60°	6.1
62.5°	5.1
65°	3.0
67.5°	2.1
70°	2.1
72.5°	1.0
75°	1.0
77.5°	1.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)