

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P210793

Luminaire Tested: **LE_4B10D010 EC4B10209727 4LBS1MW**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P210793
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B10D010 EC4B10209727 4LBS1MW
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH MATTE WHITE TRIM
WATTAGE D010TR-10.05W DE010-10.58W D5LT-10.2W DMX-10.6W DL2-11.8W
DL3-11.1W DLE-11.39W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 910.9 lumens
Efficiency: N/A
Efficacy: 92.0 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P210793

CATALOG NUMBER: LE_4B10D010 EC4B10209727 4LBS1MW

Luminous Intensity Polar Plot






TEST NUMBER: P210793

CATALOG NUMBER: LE_4B10D010 EC4B10209727 4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20				20
RC	80				70					50					30				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	0
RCR																			
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	
1	110	106	102	99	107	104	100	97	99	97	94	96	93	91	92	90	88	86	
2	101	93	87	82	98	92	86	81	88	83	79	85	81	77	82	79	76	74	
3	93	83	75	69	90	81	74	69	78	72	67	76	70	66	73	69	65	63	
4	85	74	66	59	83	72	65	59	70	63	58	68	62	57	66	61	56	54	
5	78	66	58	51	76	65	57	51	63	56	51	61	55	50	59	54	49	47	
6	73	60	51	45	71	59	51	45	57	50	44	55	49	44	54	48	44	42	
7	67	54	46	40	66	54	46	40	52	45	40	51	44	39	49	43	39	37	
8	63	50	41	36	61	49	41	36	48	41	35	46	40	35	45	39	35	33	
9	59	46	38	32	57	45	37	32	44	37	32	43	36	32	42	36	32	30	
10	55	42	34	29	54	42	34	29	41	34	29	40	33	29	39	33	29	27	

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P210793

CATALOG NUMBER: LE_4B10D010 EC4B10209727 4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	34.8	3.8
10°-20°	99.1	10.9
20°-30°	149.3	16.4
30°-40°	177.6	19.5
40°-50°	177.3	19.5
50°-60°	144.2	15.8
60°-70°	88.7	9.7
70°-80°	34.4	3.8
80°-90°	5.5	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	283.2	31.1
0°-40°	460.8	50.6
0°-60°	782.3	85.9
0°-90°	910.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	910.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	367	
5°	366	35
15°	352	99
25°	325	149
35°	284	178
45°	230	177
55°	161	144
65°	89	89
75°	31	34
85°	4	5
90°	0	



TEST NUMBER: P210793

CATALOG NUMBER: LE_4B10D010 EC4B10209727 4LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	367.0
2.5°	367.6
5°	366.0
7.5°	363.8
10°	361.1
12.5°	356.2
15°	351.9
17.5°	345.4
20°	338.4
22.5°	332.0
25°	324.9
27.5°	315.2
30°	305.5
32.5°	296.3
35°	284.4
37.5°	271.4
40°	259.6
42.5°	245.0
45°	230.5
47.5°	214.8
50°	198.1
52.5°	180.8
55°	161.4
57.5°	142.4
60°	124.1
62.5°	106.4
65°	89.1
67.5°	72.8
70°	57.8
72.5°	43.7
75°	31.3
77.5°	20.5
80°	12.4
82.5°	7.5
85°	4.3
87.5°	2.2
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)