

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211034

Luminaire Tested: **LE_4B10D010 EC4B10209050 4LBCSM1B**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211034
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B10D010 EC4B10209050 4LBSCM1B
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH CAST MATTE METALLIC SILVER TRIM
WATTAGE D010TR-10.05W DE010-10.58W D5LT-10.2W DMX-10.6W DL2-11.8W
DL3-11.1W DLE-11.39W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1060.3 lumens
Efficiency: N/A
Efficacy: 107.1 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211034

CATALOG NUMBER: LE_4B10D010 EC4B10209050 4LBCSM1B

Luminous Intensity Polar Plot





TEST NUMBER: P211034

CATALOG NUMBER: LE_4B10D010 EC4B10209050 4LBCSM1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111		106	106	106		102	102	102
1	111	107	103	100	108	104	101	98		100	98	95		96	94	92		93	91	90
2	102	95	89	84	99	93	87	83		89	85	81		86	82	79		83	80	77
3	93	84	77	71	91	83	76	70		80	74	69		77	72	68		74	70	67
4	86	75	67	61	84	74	66	61		71	65	60		69	63	59		67	62	58
5	79	67	59	53	77	66	59	53		64	57	52		62	56	52		61	55	51
6	74	61	53	47	72	60	52	46		58	51	46		57	50	46		55	50	45
7	68	55	47	41	67	55	47	41		53	46	41		52	45	41		50	45	40
8	64	51	43	37	62	50	42	37		49	42	37		48	41	37		46	41	36
9	60	47	39	33	58	46	39	33		45	38	33		44	38	33		43	37	33
10	56	43	35	30	55	43	35	30		42	35	30		41	34	30		40	34	30

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211034

CATALOG NUMBER: LE_4B10D010 EC4B10209050 4LBCSM1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	42.3	4.0
10°-20°	120.6	11.4
20°-30°	181.4	17.1
30°-40°	215.2	20.3
40°-50°	213.0	20.1
50°-60°	167.3	15.8
60°-70°	93.8	8.8
70°-80°	26.4	2.5
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	344.3	32.5
0°-40°	559.5	52.8
0°-60°	939.8	88.6
0°-90°	1060.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1060.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	448	
5°	447	42
15°	428	121
25°	394	181
35°	345	215
45°	278	213
55°	188	167
65°	94	94
75°	23	26
85°	0	0
90°	0	



TEST NUMBER: P211034

CATALOG NUMBER: LE_4B10D010 EC4B10209050 4LBCSM1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	447.8
2.5°	446.3
5°	446.9
7.5°	443.1
10°	438.6
12.5°	433.3
15°	427.9
17.5°	421.1
20°	412.0
22.5°	402.9
25°	393.7
27.5°	383.8
30°	371.0
32.5°	358.0
35°	345.1
37.5°	329.9
40°	312.4
42.5°	295.7
45°	277.5
47.5°	256.9
50°	235.6
52.5°	211.4
55°	188.5
57.5°	162.6
60°	138.4
62.5°	116.3
65°	93.5
67.5°	73.8
70°	54.8
72.5°	37.2
75°	22.9
77.5°	11.4
80°	3.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)