

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211384

Luminaire Tested: **LE_4B15D010 EC4B10208050 4LBCS1MW**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211384
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B15D010 EC4B10208050 4LBCS1MW
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH CAST MATTE WHITE TRIM
WATTAGE D010TR-14.39W DE010-14.29W D5LT-14.34W DMX-14.46W DL2-15.8W
DL3-15.28W DLE-15.432W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1873.8 lumens
Efficiency: N/A
Efficacy: 131.0 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211384

CATALOG NUMBER: LE_4B15D010 EC4B10208050 4LBCS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P211384

CATALOG NUMBER: LE_4B15D010 EC4B10208050 4LBCS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	110	106	102	99	108	104	100	97	100	97	94	96	93	91	92	90	89	87		
2	101	94	87	82	99	92	86	81	88	84	79	85	81	78	82	79	76	74		
3	93	83	75	70	90	81	74	69	79	73	68	76	71	67	73	69	65	63		
4	85	74	66	60	83	73	65	59	70	64	58	68	62	58	66	61	57	55		
5	79	66	58	52	77	65	57	51	63	56	51	61	55	50	60	54	50	48		
6	73	60	52	45	71	59	51	45	57	50	45	56	49	44	54	49	44	42		
7	68	55	46	40	66	54	46	40	52	45	40	51	44	40	50	44	39	37		
8	63	50	42	36	61	49	41	36	48	41	36	47	40	36	46	40	35	33		
9	59	46	38	33	57	45	38	32	44	37	32	43	37	32	42	36	32	30		
10	55	42	35	30	54	42	34	30	41	34	29	40	34	29	39	33	29	27		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211384

CATALOG NUMBER: LE_4B15D010 EC4B10208050 4LBCS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	72.5	3.9
10°-20°	206.4	11.0
20°-30°	310.5	16.6
30°-40°	368.0	19.6
40°-50°	366.2	19.5
50°-60°	295.2	15.8
60°-70°	178.6	9.5
70°-80°	66.3	3.5
80°-90°	9.9	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	589.5	31.5
0°-40°	957.5	51.1
0°-60°	1619.0	86.4
0°-90°	1873.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1873.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	765	
5°	762	73
15°	731	206
25°	674	311
35°	589	368
45°	477	366
55°	329	295
65°	180	179
75°	60	66
85°	8	10
90°	0	



TEST NUMBER: P211384

CATALOG NUMBER: LE_4B15D010 EC4B10208050 4LBCS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	765.4
2.5°	765.4
5°	761.9
7.5°	759.7
10°	752.8
12.5°	741.5
15°	731.3
17.5°	719.9
20°	706.3
22.5°	692.6
25°	674.4
27.5°	655.2
30°	633.6
32.5°	613.2
35°	589.3
37.5°	564.3
40°	534.8
42.5°	506.5
45°	476.9
47.5°	443.9
50°	407.6
52.5°	370.2
55°	329.3
57.5°	292.9
60°	252.1
62.5°	215.8
65°	179.5
67.5°	145.3
70°	113.6
72.5°	85.1
75°	60.2
77.5°	38.6
80°	22.7
82.5°	13.6
85°	8.0
87.5°	3.4
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)