

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211723

Luminaire Tested: **LE\_4B20D010 EC4B10208040 4LBS1WMH**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P211723  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LE\_4B20D010 EC4B10208040 4LBS1WMH  
Description: PORTFOLIO 4 INCH CYLINDER  
SHALLOW DISTRIBUTION WITH WARM HAZE TRIM  
WATTAGE D010TR-21.86W DE010-20.46W D5LT-21.24W DMX-20.89W DL2-22.5W  
DL3-21.8 6W DLE-22.46W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 2422.7 lumens  
Efficiency: N/A  
Efficacy: 116.5 lumens/watt  
Spacing Criteria (0/90/45): 0.99 / 0.99 / 1.08  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 20.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P211723

CATALOG NUMBER: LE\_4B20D010 EC4B10208040 4LBS1WMH

### Luminous Intensity Polar Plot





TEST NUMBER: P211723

CATALOG NUMBER: LE\_4B20D010 EC4B10208040 4LBS1WMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	108	105	102	109	106	103	101	102	100	97	98	96	94	95	93	92	90			
2	104	98	92	88	102	96	91	87	92	88	85	89	86	83	86	84	81	79			
3	96	88	82	76	94	87	81	76	84	79	74	81	77	73	79	75	72	70			
4	90	80	73	67	88	79	72	67	76	70	66	74	69	65	72	68	64	62			
5	83	73	65	59	82	72	64	59	70	63	59	68	62	58	66	61	57	56			
6	78	66	59	53	76	65	58	53	64	57	53	62	57	52	61	56	52	50			
7	73	61	53	48	71	60	53	48	59	52	48	57	52	47	56	51	47	45			
8	68	56	49	44	67	56	48	43	54	48	43	53	47	43	52	47	43	41			
9	64	52	45	40	63	52	45	40	50	44	40	49	44	39	49	43	39	38			
10	60	48	41	37	59	48	41	37	47	41	36	46	40	36	45	40	36	35			

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P211723

CATALOG NUMBER: LE\_4B20D010 EC4B10208040 4LBS1WMH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	141.9	5.9
10°-20°	376.1	15.5
20°-30°	505.1	20.8
30°-40°	517.0	21.3
40°-50°	447.5	18.5
50°-60°	297.6	12.3
60°-70°	122.2	5.0
70°-80°	14.6	0.6
80°-90°	0.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1023.1	42.2
0°-40°	1540.2	63.6
0°-60°	2285.3	94.3
0°-90°	2422.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2422.7	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1536	
5°	1512	142
15°	1343	376
25°	1102	505
35°	826	517
45°	583	448
55°	330	298
65°	121	122
75°	6	15
85°	0	1
90°	0	



TEST NUMBER: P211723

CATALOG NUMBER: LE\_4B20D010 EC4B10208040 4LBS1WMH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1535.5
2.5°	1532.4
5°	1511.7
7.5°	1479.9
10°	1437.1
12.5°	1389.4
15°	1343.4
17.5°	1284.7
20°	1227.5
22.5°	1167.2
25°	1102.0
27.5°	1032.2
30°	962.3
32.5°	892.4
35°	825.7
37.5°	762.2
40°	701.9
42.5°	641.5
45°	582.8
47.5°	520.8
50°	457.3
52.5°	393.8
55°	330.3
57.5°	274.7
60°	217.5
62.5°	165.2
65°	120.6
67.5°	79.3
70°	46.1
72.5°	22.3
75°	6.4
77.5°	3.1
80°	1.6
82.5°	1.6
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)