

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211928

Luminaire Tested: **LE_4B30D010 EC4B30509727 4LBW1GPH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211928
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B30D010 EC4B30509727 4LBW1GPH
Description: PORTFOLIO 4 INCH CYLINDER
WIDE DISTRIBUTIONWITH GRAPHITE HAZE TRIM
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W
DL3-29.67W DLE-29.73W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1582.2 lumens
Efficiency: N/A
Efficacy: 56.5 lumens/watt
Spacing Criteria (0/90/45): 1.12 / 1.12 / 1.08
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211928

CATALOG NUMBER: LE_4B30D010 EC4B30509727 4LBW1GPH

Luminous Intensity Polar Plot





TEST NUMBER: P211928

CATALOG NUMBER: LE_4B30D010 EC4B30509727 4LBW1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	110	107	104	110	107	105	103	103	101	99	100	98	96	96	95	94	92			
2	106	100	96	92	104	99	95	91	95	92	89	92	90	87	90	87	85	83			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	77	76			
4	94	85	78	74	92	84	78	73	81	76	72	79	75	71	77	74	71	69			
5	88	78	72	67	86	77	71	66	75	70	66	74	69	65	72	68	64	63			
6	83	72	65	61	81	71	65	60	70	64	60	68	63	59	67	63	59	57			
7	78	67	60	55	76	66	60	55	65	59	55	64	58	55	63	58	54	53			
8	73	62	56	51	72	62	55	51	61	55	50	59	54	50	58	54	50	48			
9	69	58	51	47	68	58	51	47	57	51	47	56	50	46	55	50	46	45			
10	65	54	48	43	64	54	48	43	53	47	43	52	47	43	51	46	43	41			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211928

CATALOG NUMBER: LE_4B30D010 EC4B30509727 4LBW1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	107.4	6.8
10°-20°	304.4	19.2
20°-30°	436.6	27.6
30°-40°	411.0	26.0
40°-50°	227.0	14.3
50°-60°	72.8	4.6
60°-70°	18.2	1.2
70°-80°	4.4	0.3
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	848.4	53.6
0°-40°	1259.4	79.6
0°-60°	1559.2	98.5
0°-90°	1582.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1582.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1139	
5°	1133	107
15°	1078	304
25°	958	437
35°	667	411
45°	288	227
55°	74	73
65°	16	18
75°	3	4
85°	0	0
90°	0	



TEST NUMBER: P211928

CATALOG NUMBER: LE_4B30D010 EC4B30509727 4LBW1GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	1138.8
2.5°	1130.5
5°	1133.2
7.5°	1125.0
10°	1111.3
12.5°	1097.6
15°	1078.3
17.5°	1061.9
20°	1034.5
22.5°	996.1
25°	957.7
27.5°	905.5
30°	836.9
32.5°	760.0
35°	666.8
37.5°	568.1
40°	466.4
42.5°	373.2
45°	288.1
47.5°	216.8
50°	156.4
52.5°	109.7
55°	74.1
57.5°	49.4
60°	35.7
62.5°	24.7
65°	16.5
67.5°	11.0
70°	8.2
72.5°	5.5
75°	2.8
77.5°	2.8
80°	2.8
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)