

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211959

Luminaire Tested: **LE_4B30D010 EC4B30508030 4LBW1LI**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211959
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B30D010 EC4B30508030 4LBW1LI
Description: PORTFOLIO 4 INCH CYLINDER
WIDE DISTRIBUTION WITH SPECULAR CLEAR TRIM
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W
DL3-29.67W DLE-29.73W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3351.9 lumens
Efficiency: N/A
Efficacy: 119.7 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.18
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211959

CATALOG NUMBER: LE_4B30D010 EC4B30508030 4LBW1LI

Luminous Intensity Polar Plot





TEST NUMBER: P211959

CATALOG NUMBER: LE_4B30D010 EC4B30508030 4LBW1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92	92	92	92
2	106	101	97	93	104	99	95	92	96	93	90	93	90	88	90	88	86	84	84	84	84
3	100	93	87	83	98	92	86	82	89	85	81	86	83	80	84	81	78	77	77	77	77
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	72	70	70	70	70
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64	64	64	64
6	83	73	66	62	82	72	66	61	71	65	61	69	64	60	68	63	60	58	58	58	58
7	78	68	61	56	77	67	61	56	66	60	56	64	59	55	63	59	55	54	54	54	54
8	74	63	56	52	72	62	56	51	61	55	51	60	55	51	59	54	51	49	49	49	49
9	69	59	52	48	68	58	52	47	57	51	47	56	51	47	55	50	47	45	45	45	45
10	66	55	48	44	65	54	48	44	53	48	44	53	47	44	52	47	43	42	42	42	42

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211959

CATALOG NUMBER: LE_4B30D010 EC4B30508030 4LBW1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	200.8	6.0
10°-20°	633.8	18.9
20°-30°	988.8	29.5
30°-40°	962.1	28.7
40°-50°	480.5	14.3
50°-60°	74.4	2.2
60°-70°	9.0	0.3
70°-80°	2.5	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1823.4	54.4
0°-40°	2785.5	83.1
0°-60°	3340.4	99.7
0°-90°	3351.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3351.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2054	
5°	2081	201
15°	2238	634
25°	2173	989
35°	1562	962
45°	603	481
55°	61	74
65°	8	9
75°	4	2
85°	0	0
90°	0	



TEST NUMBER: P211959

CATALOG NUMBER: LE_4B30D010 EC4B30508030 4LBW1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	2053.8
2.5°	2061.4
5°	2080.7
7.5°	2111.3
10°	2149.7
12.5°	2199.6
15°	2238.0
17.5°	2268.7
20°	2272.6
22.5°	2245.8
25°	2172.8
27.5°	2065.3
30°	1930.9
32.5°	1762.0
35°	1562.4
37.5°	1343.6
40°	1113.3
42.5°	867.6
45°	602.7
47.5°	387.7
50°	234.2
52.5°	126.7
55°	61.4
57.5°	26.9
60°	15.3
62.5°	11.5
65°	7.7
67.5°	7.7
70°	3.8
72.5°	3.8
75°	3.8
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)