

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211973

Luminaire Tested: **LE_4B30D010 EC4B30509030 4LBN1H**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211973
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B30D010 EC4B30509030 4LBN1H
Description: PORTFOLIO 4 INCH CYLINDER
NARROW DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W
DL3-29.67W DLE-29.73W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1806.7 lumens
Efficiency: N/A
Efficacy: 64.5 lumens/watt
Spacing Criteria (0/90/45): 0.81 / 0.81 / 0.85
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211973

CATALOG NUMBER: LE_4B30D010 EC4B30509030 4LBN1H

Luminous Intensity Polar Plot





TEST NUMBER: P211973

CATALOG NUMBER: LE_4B30D010 EC4B30509030 4LBN1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20																	
RC	80									70									50									30									10									0								
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																								
RCR																																																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																																				
1	113	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	93	93	93	93	93	93	93	93	93	93	93	93	93	93	93	93	93																				
2	108	103	99	96	106	101	98	94	98	95	92	95	93	90	92	90	89	87	87	87	87	87	87	87	87	87	87	87	87	87	87	87	87	87	87																			
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81	81	81	81	81	81	81	81	81	81	81	81	81	81	81	81	81	81																			
4	97	90	84	80	95	89	83	79	86	82	78	84	81	78	83	79	77	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75																			
5	92	84	78	74	91	83	78	73	81	76	73	80	75	72	78	74	72	70	70	70	70	70	70	70	70	70	70	70	70	70	70	70	70	70	70																			
6	88	79	73	69	86	78	72	68	77	72	68	75	71	67	74	70	67	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65																			
7	83	74	68	64	82	73	68	64	72	67	63	71	66	63	70	66	63	61	61	61	61	61	61	61	61	61	61	61	61	61	61	61	61	61	61																			
8	79	70	64	60	78	69	64	60	68	63	59	67	63	59	66	62	59	57	57	57	57	57	57	57	57	57	57	57	57	57	57	57	57	57	57																			
9	76	66	60	56	74	65	60	56	65	59	56	64	59	56	63	59	55	53	53	53	53	53	53	53	53	53	53	53	53	53	53	53	53	53	53																			
10	72	62	57	53	71	62	56	53	61	56	53	60	56	52	60	55	52	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211973

CATALOG NUMBER: LE_4B30D010 EC4B30509030 4LBN1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	204.7	11.3
10°-20°	496.5	27.5
20°-30°	576.4	31.9
30°-40°	381.7	21.1
40°-50°	107.1	5.9
50°-60°	26.9	1.5
60°-70°	10.1	0.6
70°-80°	3.4	0.2
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1277.6	70.7
0°-40°	1659.3	91.8
0°-60°	1793.3	99.3
0°-90°	1806.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1806.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2268	
5°	2210	205
15°	1778	496
25°	1264	576
35°	612	382
45°	124	107
55°	30	27
65°	10	10
75°	3	3
85°	0	0
90°	0	



TEST NUMBER: P211973

CATALOG NUMBER: LE_4B30D010 EC4B30509030 4LBN1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	2268.4
2.5°	2258.6
5°	2209.6
7.5°	2124.4
10°	2019.7
12.5°	1901.8
15°	1777.5
17.5°	1656.4
20°	1522.2
22.5°	1397.7
25°	1263.5
27.5°	1135.9
30°	972.2
32.5°	798.7
35°	612.1
37.5°	438.6
40°	297.9
42.5°	193.1
45°	124.4
47.5°	75.3
50°	49.1
52.5°	36.0
55°	29.5
57.5°	23.0
60°	16.4
62.5°	13.1
65°	9.9
67.5°	6.5
70°	6.5
72.5°	3.2
75°	3.2
77.5°	3.2
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)