

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P212086

Luminaire Tested: **LE_4B30D010 EC4B30508040 4LBM1WH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P212086
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B30D010 EC4B30508040 4LBM1WH
Description: PORTFOLIO 4 INCH CYLINDER
MEDIUM DISTRIBUTION WITH WHEAT TRIM
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W
DL3-29.67W DLE-29.73W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2692.4 lumens
Efficiency: N/A
Efficacy: 96.2 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.87
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P212086

CATALOG NUMBER: LE_4B30D010 EC4B30508040 4LBM1WH

Luminous Intensity Polar Plot





TEST NUMBER: P212086

CATALOG NUMBER: LE_4B30D010 EC4B30508040 4LBM1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	108	106	111	109	106	105	105	103	101	101	100	98	98	96	95	94		
2	108	103	99	96	106	102	98	95	98	95	93	95	93	91	93	91	89	87		
3	103	96	91	88	101	95	90	87	92	89	85	90	87	84	88	85	83	81		
4	98	90	85	81	96	89	84	80	87	83	79	85	81	78	83	80	77	76		
5	93	84	79	74	91	84	78	74	82	77	73	80	76	73	79	75	72	71		
6	88	79	73	69	87	79	73	69	77	72	68	76	71	68	74	71	68	66		
7	84	75	69	65	82	74	68	64	73	68	64	72	67	64	70	66	63	62		
8	80	70	64	60	79	70	64	60	69	64	60	68	63	60	67	63	59	58		
9	76	66	61	57	75	66	60	57	65	60	56	64	60	56	63	59	56	55		
10	73	63	57	53	72	62	57	53	62	57	53	61	56	53	60	56	53	52		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P212086

CATALOG NUMBER: LE_4B30D010 EC4B30508040 4LBM1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	295.4	11.0
10°-20°	759.5	28.2
20°-30°	891.1	33.1
30°-40°	563.9	20.9
40°-50°	151.0	5.6
50°-60°	21.1	0.8
60°-70°	7.8	0.3
70°-80°	2.6	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1946.0	72.3
0°-40°	2509.9	93.2
0°-60°	2682.0	99.6
0°-90°	2692.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2692.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3198	
5°	3146	295
15°	2720	759
25°	1969	891
35°	895	564
45°	171	151
55°	20	21
65°	8	8
75°	4	3
85°	0	0
90°	0	



TEST NUMBER: P212086

CATALOG NUMBER: LE_4B30D010 EC4B30508040 4LBM1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	3197.8
2.5°	3185.8
5°	3146.0
7.5°	3082.4
10°	2990.9
12.5°	2871.6
15°	2720.4
17.5°	2565.3
20°	2378.5
22.5°	2187.5
25°	1968.8
27.5°	1730.1
30°	1463.7
32.5°	1173.3
35°	894.9
37.5°	648.3
40°	445.4
42.5°	286.4
45°	171.0
47.5°	95.5
50°	51.7
52.5°	27.8
55°	19.8
57.5°	15.9
60°	11.9
62.5°	11.9
65°	8.0
67.5°	3.9
70°	3.9
72.5°	3.9
75°	3.9
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)