

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P212129

Luminaire Tested: **LE_4B30D010 EC4B30509040 4LBS1WMH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P212129
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B30D010 EC4B30509040 4LBS1WMH
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH WARM HAZE TRIM
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W
DL3-29.67W DLE-29.73W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2924.7 lumens
Efficiency: N/A
Efficacy: 104.5 lumens/watt
Spacing Criteria (0/90/45): 0.99 / 0.99 / 1.08
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P212129

CATALOG NUMBER: LE_4B30D010 EC4B30509040 4LBS1WMH

Luminous Intensity Polar Plot





TEST NUMBER: P212129

CATALOG NUMBER: LE_4B30D010 EC4B30509040 4LBS1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	108	105	102	109	106	103	101	102	100	97	98	96	94	95	93	92	90			
2	104	98	92	88	102	96	91	87	92	88	85	89	86	83	86	84	81	79			
3	96	88	82	76	94	87	81	76	84	79	74	81	77	73	79	75	72	70			
4	90	80	73	67	88	79	72	67	76	70	66	74	69	65	72	68	64	62			
5	83	73	65	59	82	72	64	59	70	63	59	68	62	58	66	61	57	56			
6	78	66	59	53	76	65	58	53	64	57	53	62	57	52	61	56	52	50			
7	73	61	53	48	71	60	53	48	59	52	48	57	52	47	56	51	47	45			
8	68	56	49	44	67	56	48	43	54	48	43	53	47	43	52	47	43	41			
9	64	52	45	40	63	52	45	40	50	44	40	49	44	39	49	43	39	38			
10	60	48	41	37	59	48	41	37	47	41	36	46	40	36	45	40	36	35			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P212129

CATALOG NUMBER: LE_4B30D010 EC4B30509040 4LBS1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	171.3	5.9
10°-20°	454.0	15.5
20°-30°	609.7	20.8
30°-40°	624.1	21.3
40°-50°	540.2	18.5
50°-60°	359.3	12.3
60°-70°	147.6	5.0
70°-80°	17.5	0.6
80°-90°	0.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1235.1	42.2
0°-40°	1859.2	63.6
0°-60°	2758.8	94.3
0°-90°	2924.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2924.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1854	
5°	1825	171
15°	1622	454
25°	1330	610
35°	997	624
45°	704	540
55°	399	359
65°	146	148
75°	8	18
85°	0	1
90°	0	



TEST NUMBER: P212129

CATALOG NUMBER: LE_4B30D010 EC4B30509040 4LBS1WMH

CANDELA DISTRIBUTION (FULL):

	0°
0°	1853.7
2.5°	1849.9
5°	1824.9
7.5°	1786.6
10°	1734.8
12.5°	1677.4
15°	1621.7
17.5°	1550.8
20°	1481.8
22.5°	1408.9
25°	1330.4
27.5°	1246.0
30°	1161.6
32.5°	1077.3
35°	996.8
37.5°	920.1
40°	847.3
42.5°	774.4
45°	703.5
47.5°	628.7
50°	552.0
52.5°	475.4
55°	398.7
57.5°	331.6
60°	262.6
62.5°	199.4
65°	145.7
67.5°	95.8
70°	55.6
72.5°	26.8
75°	7.7
77.5°	3.8
80°	2.0
82.5°	2.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)