

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P212158

Luminaire Tested: **LE\_4B30D010 EC4B30508050 4LBS1WMH**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P212158  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LE\_4B30D010 EC4B30508050 4LBS1WMH  
Description: PORTFOLIO 4 INCH CYLINDER  
SHALLOW DISTRIBUTION WITH WARM HAZE TRIM  
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W  
DL3-29.67W DLE-29.73W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 3489.4 lumens  
Efficiency: N/A  
Efficacy: 124.6 lumens/watt  
Spacing Criteria (0/90/45): 0.99 / 0.99 / 1.08  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 28  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P212158

CATALOG NUMBER: LE\_4B30D010 EC4B30508050 4LBS1WMH

### Luminous Intensity Polar Plot





TEST NUMBER: P212158

CATALOG NUMBER: LE\_4B30D010 EC4B30508050 4LBS1WMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	102	109	106	103	101	102	100	97	98	96	94	95	93	92	90
2	104	98	92	88	102	96	91	87	92	88	85	89	86	83	86	84	81	79
3	96	88	82	76	94	87	81	76	84	79	74	81	77	73	79	75	72	70
4	90	80	73	67	88	79	72	67	76	70	66	74	69	65	72	68	64	62
5	83	73	65	59	82	72	64	59	70	63	59	68	62	58	66	61	57	56
6	78	66	59	53	76	65	58	53	64	57	53	62	57	52	61	56	52	50
7	73	61	53	48	71	60	53	48	59	52	48	57	52	47	56	51	47	45
8	68	56	49	44	67	56	48	43	54	48	43	53	47	43	52	47	43	41
9	64	52	45	40	63	52	45	40	50	44	40	49	44	39	49	43	39	38
10	60	48	41	37	59	48	41	37	47	41	36	46	40	36	45	40	36	35

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P212158

CATALOG NUMBER: LE\_4B30D010 EC4B30508050 4LBS1WMH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	204.4	5.9
10°-20°	541.7	15.5
20°-30°	727.5	20.8
30°-40°	744.6	21.3
40°-50°	644.5	18.5
50°-60°	428.7	12.3
60°-70°	176.1	5.0
70°-80°	20.9	0.6
80°-90°	0.9	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1473.5	42.2
0°-40°	2218.2	63.6
0°-60°	3291.4	94.3
0°-90°	3489.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3489.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2212	
5°	2177	204
15°	1935	542
25°	1587	727
35°	1189	745
45°	839	645
55°	476	429
65°	174	176
75°	9	21
85°	0	1
90°	0	



TEST NUMBER: P212158

CATALOG NUMBER: LE\_4B30D010 EC4B30508050 4LBS1WMH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	2211.5
2.5°	2207.0
5°	2177.3
7.5°	2131.5
10°	2069.8
12.5°	2001.1
15°	1934.9
17.5°	1850.2
20°	1767.8
22.5°	1681.0
25°	1587.2
27.5°	1486.5
30°	1386.0
32.5°	1285.3
35°	1189.2
37.5°	1097.8
40°	1010.8
42.5°	923.9
45°	839.4
47.5°	750.2
50°	658.6
52.5°	567.2
55°	475.7
57.5°	395.7
60°	313.3
62.5°	237.8
65°	173.8
67.5°	114.4
70°	66.4
72.5°	32.0
75°	9.2
77.5°	4.5
80°	2.3
82.5°	2.3
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)