

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P170668

Luminaire Tested: **LDA4A13940D010TE LAR35FL 4LFC1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P170668  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P26143)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LDA4A13940D010TE LAR35FL 4LFC1  
Description: PORTFOLIO 4" Flat Cone, Self-flange Trim Ring, 35° Flood Optic, at 0° tilt  
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1529.5 lumens  
Efficiency: N/A  
Efficacy: 68.7 lumens/watt  
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.56  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct


Input Watts (W): 22.27  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P170668

CATALOG NUMBER: LDA4A13940D010TE LAR35FL 4LFC1

### Luminous Intensity Polar Plot





TEST NUMBER: P170668

CATALOG NUMBER: LDA4A13940D010TE LAR35FL 4LFC1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	113	111	109	107	107	105	104	103	102	101	100	99	98	96
2	111	107	104	102	109	106	103	101	103	100	99	100	98	96	97	96	94	93
3	107	103	99	96	106	101	98	95	99	96	94	97	94	92	95	93	91	90
4	104	99	94	91	102	97	94	91	95	92	90	94	91	89	92	90	88	87
5	101	95	91	87	99	94	90	87	92	89	86	91	88	86	89	87	85	84
6	98	91	87	84	96	91	87	84	89	86	83	88	85	83	87	84	82	81
7	95	88	84	81	94	87	83	81	86	83	80	85	82	80	84	82	79	78
8	92	85	81	78	91	85	81	78	84	80	78	83	80	77	82	79	77	76
9	89	82	78	75	88	82	78	75	81	78	75	80	77	75	80	77	75	74
10	87	80	76	73	86	79	76	73	79	75	73	78	75	72	78	75	72	71

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	580551
5°	572739
10°	472863
15°	381239
20°	246706
25°	60223
30°	14471
35°	3644
40°	1143
45°	244
50°	134
55°	0
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P170668

CATALOG NUMBER: LDA4A13940D010TE LAR35FL 4LFC1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	409.7	26.8
10°-20°	800.7	52.4
20°-30°	296.3	19.4
30°-40°	20.9	1.4
40°-50°	1.8	0.1
50°-60°	0.1	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1506.8	98.5
0°-40°	1527.6	99.9
0°-60°	1529.5	100.0
0°-90°	1529.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1529.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4707	
5°	4626	410
15°	2986	801
25°	442	296
35°	24	21
45°	1	2
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P170668

CATALOG NUMBER: LDA4A13940D010TE LAR35FL 4LFC1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	4706.7
1°	4679.0
2°	4664.1
3°	4693.2
4°	4700.3
5°	4625.7
6°	4492.9
7°	4307.5
8°	4119.9
9°	3934.5
10°	3775.4
11°	3604.2
12°	3452.9
13°	3302.3
14°	3149.6
15°	2985.5
17.5°	2494.0
20°	1879.5
22.5°	1162.8
25°	442.5
27.5°	181.8
30°	101.6
32.5°	48.3
35°	24.2
37.5°	12.8
40°	7.1
42.5°	3.6
45°	1.4
47.5°	0.7
50°	0.7
52.5°	0.0
55°	0.0
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P170668

CATALOG NUMBER: LDA4A13940D010TE LAR35FL 4LFC1

**CANDELA DISTRIBUTION (continued):**

0°  
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)