

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P274295

Luminaire Tested: **LD4B10DE010W2N2765 EU4B1020W2N902765 4LBS0LI**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P274295  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35292)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LD4B10DE010W2N2765 EU4B1020W2N902765 4LBS0LI  
Description: PORTFOLIO 4" W2N RN DOWNLIGHT, SHALLOW WITH SPECULAR FINISH  
Light Source: W2N 2700K-6500K CCT TUNING RANGE  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1056.0 lumens  
Efficiency: N/A  
Efficacy: 75.4 lumens/watt  
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct


Input Watts (W): 14  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P274295

CATALOG NUMBER: LD4B10DE010W2N2765 EU4B1020W2N902765 4LBSOLI

### Luminous Intensity Polar Plot





TEST NUMBER: P274295

CATALOG NUMBER: LD4B10DE010W2N2765 EU4B1020W2N902765 4LBSOLI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	102	109	106	103	101	102	100	98	98	96	95	95	93	92	90
2	104	98	93	88	102	96	91	87	93	89	85	90	86	84	87	84	82	80
3	97	89	82	77	95	87	81	77	84	79	75	82	78	74	79	76	73	71
4	90	81	73	68	88	79	73	68	77	71	67	75	70	66	73	69	65	63
5	84	73	66	61	82	72	65	60	70	64	60	69	63	59	67	62	59	57
6	79	67	60	54	77	66	59	54	65	58	54	63	58	53	62	57	53	51
7	74	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	44	41	39
10	61	50	43	38	60	49	42	38	48	42	38	47	42	38	46	41	37	36

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	82383
5°	80515
10°	75610
15°	70346
20°	65241
25°	59470
30°	52951
35°	46937
40°	42190
45°	37749
50°	32381
55°	26059
60°	19405
65°	12384
70°	5974
75°	971
80°	755
85°	0



TEST NUMBER: P274295

CATALOG NUMBER: LD4B10DE010W2N2765 EU4B1020W2N902765 4LBSOLI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	68.4	6.5
10°-20°	174.4	16.5
20°-30°	225.9	21.4
30°-40°	221.4	21.0
40°-50°	187.6	17.8
50°-60°	123.0	11.6
60°-70°	49.4	4.7
70°-80°	5.7	0.5
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	468.7	44.4
0°-40°	690.1	65.3
0°-60°	1000.7	94.8
0°-90°	1056.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1056.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	754	
5°	734	68
15°	622	174
25°	493	226
35°	352	221
45°	244	188
55°	137	123
65°	48	49
75°	2	6
85°	0	0
90°	0	



TEST NUMBER: P274295

CATALOG NUMBER: LD4B10DE010W2N2765 EU4B1020W2N902765 4LBSOLI

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	754.0
2.5°	748.2
5°	734.1
7.5°	710.8
10°	681.5
12.5°	650.0
15°	621.9
17.5°	591.5
20°	561.1
22.5°	528.4
25°	493.3
27.5°	457.1
30°	419.7
32.5°	384.6
35°	351.9
37.5°	325.0
40°	295.8
42.5°	270.0
45°	244.3
47.5°	217.4
50°	190.5
52.5°	163.7
55°	136.8
57.5°	112.2
60°	88.8
62.5°	67.8
65°	47.9
67.5°	31.6
70°	18.7
72.5°	8.2
75°	2.3
77.5°	1.2
80°	1.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)