

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P210851

Luminaire Tested: **LSR4B10D010BZ EC4B10209030 4LBSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P210851
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B10D010BZ EC4B10209030 4LBSMW1
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH MATTE WHITE TRIM
WATTAGE D010TR-10.05W DE010-10.58W D5LT-10.2W DMX-10.6W DL2-11.8W
DL3-11.1W DLE-11.39W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 939.2 lumens
Efficiency: N/A
Efficacy: 94.9 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P210851

CATALOG NUMBER: LSR4B10D010BZ EC4B10209030 4LBSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P210851

CATALOG NUMBER: LSR4B10D010BZ EC4B10209030 4LBSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	110	106	102	99	107	104	100	97	99	97	94	96	93	91	92	90	88	86																			
2	101	93	87	82	98	92	86	81	88	83	79	85	81	77	82	79	76	74																			
3	93	83	75	69	90	81	74	69	78	72	67	76	70	66	73	69	65	63																			
4	85	74	66	59	83	72	65	59	70	63	58	68	62	57	66	61	56	54																			
5	78	66	58	51	76	65	57	51	63	56	51	61	55	50	59	54	49	47																			
6	73	60	51	45	71	59	51	45	57	50	44	55	49	44	54	48	44	42																			
7	67	54	46	40	66	54	46	40	52	45	40	51	44	39	49	43	39	37																			
8	63	50	41	36	61	49	41	36	48	41	35	46	40	35	45	39	35	33																			
9	59	46	38	32	57	45	37	32	44	37	32	43	36	32	42	36	32	30																			
10	55	42	34	29	54	42	34	29	41	34	29	40	33	29	39	33	29	27																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P210851

CATALOG NUMBER: LSR4B10D010BZ EC4B10209030 4LBSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	35.9	3.8
10°-20°	102.2	10.9
20°-30°	153.9	16.4
30°-40°	183.2	19.5
40°-50°	182.8	19.5
50°-60°	148.7	15.8
60°-70°	91.4	9.7
70°-80°	35.4	3.8
80°-90°	5.7	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	292.0	31.1
0°-40°	475.1	50.6
0°-60°	806.6	85.9
0°-90°	939.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	939.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	378	
5°	377	36
15°	363	102
25°	335	154
35°	293	183
45°	238	183
55°	166	149
65°	92	91
75°	32	35
85°	4	6
90°	0	



TEST NUMBER: P210851

CATALOG NUMBER: LSR4B10D010BZ EC4B10209030 4LBSMW1

CANDELA DISTRIBUTION (FULL):

0°	
0°	378.4
2.5°	379.0
5°	377.3
7.5°	375.1
10°	372.3
12.5°	367.3
15°	362.8
17.5°	356.2
20°	348.9
22.5°	342.2
25°	335.0
27.5°	325.0
30°	315.0
32.5°	305.5
35°	293.3
37.5°	279.9
40°	267.7
42.5°	252.6
45°	237.6
47.5°	221.5
50°	204.2
52.5°	186.4
55°	166.4
57.5°	146.9
60°	128.0
62.5°	109.6
65°	91.8
67.5°	75.1
70°	59.5
72.5°	45.1
75°	32.3
77.5°	21.1
80°	12.8
82.5°	7.8
85°	4.5
87.5°	2.2
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)