

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211195

Luminaire Tested: **LSR4B15D010BZ EC4B10208030 4LBSB1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P211195  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR4B15D010BZ EC4B10208030 4LBSB1  
Description: PORTFOLIO 4 INCH CYLINDER  
SHALLOW DISTRIBUTION WITH SPECULAR BLACK TRIM  
WATTAGE D010TR-14.39W DE010-14.29W D5LT-14.34W DMX-14.46W DL2-15.8W  
DL3-15.28W DLE-15.432W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1290.6 lumens  
Efficiency: N/A  
Efficacy: 90.3 lumens/watt  
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.3  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 14.3  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P211195

CATALOG NUMBER: LSR4B15D010BZ EC4B10208030 4LBSB1

### Luminous Intensity Polar Plot





TEST NUMBER: P211195

CATALOG NUMBER: LSR4B15D010BZ EC4B10208030 4LBSB1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	111	107	103	100	108	105	101	98	100	98	95	97	94	93	93	91	90	88																			
2	102	95	89	84	100	93	88	83	90	85	81	86	83	79	84	80	78	76																			
3	94	84	77	72	91	83	76	71	80	74	70	77	73	68	75	71	67	65																			
4	86	76	68	62	84	74	67	61	72	65	60	70	64	60	68	63	59	57																			
5	80	68	60	54	78	67	59	53	65	58	53	63	57	52	61	56	52	50																			
6	74	62	53	47	72	61	53	47	59	52	47	57	51	46	56	50	46	44																			
7	69	56	48	42	67	55	48	42	54	47	42	52	46	41	51	45	41	39																			
8	64	51	43	38	63	51	43	38	49	42	37	48	42	37	47	41	37	35																			
9	60	47	39	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32																			
10	56	44	36	31	55	43	36	31	42	36	31	41	35	31	40	35	31	29																			

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P211195

CATALOG NUMBER: LSR4B15D010BZ EC4B10208030 4LBSB1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	53.7	4.2
10°-20°	152.5	11.8
20°-30°	226.8	17.6
30°-40°	263.9	20.4
40°-50°	257.2	19.9
50°-60°	197.9	15.3
60°-70°	109.4	8.5
70°-80°	29.0	2.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	433.0	33.6
0°-40°	696.9	54.0
0°-60°	1152.0	89.3
0°-90°	1290.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1290.6	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	569	
5°	566	54
15°	540	152
25°	492	227
35°	424	264
45°	334	257
55°	221	198
65°	110	109
75°	24	29
85°	0	0
90°	0	



TEST NUMBER: P211195

CATALOG NUMBER: LSR4B15D010BZ EC4B10208030 4LBSB1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	569.3
2.5°	569.3
5°	566.1
7.5°	561.2
10°	557.9
12.5°	548.1
15°	539.9
17.5°	531.7
20°	520.3
22.5°	508.8
25°	492.4
27.5°	476.1
30°	459.7
32.5°	441.7
35°	423.7
37.5°	400.8
40°	381.2
42.5°	359.9
45°	333.7
47.5°	309.2
50°	281.4
52.5°	251.9
55°	220.9
57.5°	191.4
60°	163.6
62.5°	135.8
65°	109.6
67.5°	85.1
70°	62.2
72.5°	42.5
75°	24.5
77.5°	11.5
80°	1.6
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)