

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211203

Luminaire Tested: **LSR4B15D010BZ EC4B10208030 4LBWGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211203
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B15D010BZ EC4B10208030 4LBWGPH1
Description: PORTFOLIO 4 INCH CYLINDER
WIDE DISTRIBUTIONWITH GRAPHITE HAZE TRIM
WATTAGE D010TR-14.39W DE010-14.29W D5LT-14.34W DMX-14.46W DL2-15.8W
DL3-15.28W DLE-15.432W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 978.5 lumens
Efficiency: N/A
Efficacy: 68.4 lumens/watt
Spacing Criteria (0/90/45): 1.12 / 1.12 / 1.08
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211203

CATALOG NUMBER: LSR4B15D010BZ EC4B10208030 4LBWGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P211203

CATALOG NUMBER: LSR4B15D010BZ EC4B10208030 4LBWGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	110	107	104	110	107	105	103	103	101	99	100	98	96	96	95	94	92			
2	106	100	96	92	104	99	95	91	95	92	89	92	90	87	90	87	85	83			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	77	76			
4	94	85	78	74	92	84	78	73	81	76	72	79	75	71	77	74	71	69			
5	88	78	72	67	86	77	71	66	75	70	66	74	69	65	72	68	64	63			
6	83	72	65	61	81	71	65	60	70	64	60	68	63	59	67	63	59	57			
7	78	67	60	55	76	66	60	55	65	59	55	64	58	55	63	58	54	53			
8	73	62	56	51	72	62	55	51	61	55	50	59	54	50	58	54	50	48			
9	69	58	51	47	68	58	51	47	57	51	47	56	50	46	55	50	46	45			
10	65	54	48	43	64	54	48	43	53	47	43	52	47	43	51	46	43	41			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211203

CATALOG NUMBER: LSR4B15D010BZ EC4B10208030 4LBWGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	66.4	6.8
10°-20°	188.3	19.2
20°-30°	270.0	27.6
30°-40°	254.2	26.0
40°-50°	140.4	14.3
50°-60°	45.0	4.6
60°-70°	11.3	1.2
70°-80°	2.7	0.3
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	524.6	53.6
0°-40°	778.9	79.6
0°-60°	964.3	98.5
0°-90°	978.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	978.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	704	
5°	701	66
15°	667	188
25°	592	270
35°	412	254
45°	178	140
55°	46	45
65°	10	11
75°	2	3
85°	0	0
90°	0	



TEST NUMBER: P211203

CATALOG NUMBER: LSR4B15D010BZ EC4B10208030 4LBWGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	704.2
2.5°	699.1
5°	700.8
7.5°	695.7
10°	687.3
12.5°	678.8
15°	666.9
17.5°	656.7
20°	639.7
22.5°	616.0
25°	592.2
27.5°	560.0
30°	517.6
32.5°	470.1
35°	412.4
37.5°	351.3
40°	288.5
42.5°	230.8
45°	178.2
47.5°	134.1
50°	96.7
52.5°	67.9
55°	45.8
57.5°	30.5
60°	22.1
62.5°	15.3
65°	10.2
67.5°	6.8
70°	5.1
72.5°	3.4
75°	1.7
77.5°	1.7
80°	1.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)