

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211493

Luminaire Tested: **LSR4B20D010BZ EC4B10208027 4LBWGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211493
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B20D010BZ EC4B10208027 4LBWGPH1
Description: PORTFOLIO 4 INCH CYLINDER
WIDE DISTRIBUTIONWITH GRAPHITE HAZE TRIM
WATTAGE D010TR-21.86W DE010-20.46W D5LT-21.24W DMX-20.89W DL2-22.5W
DL3-21.8 6W DLE-22.46W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1268.1 lumens
Efficiency: N/A
Efficacy: 61.0 lumens/watt
Spacing Criteria (0/90/45): 1.12 / 1.12 / 1.08
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211493

CATALOG NUMBER: LSR4B20D010BZ EC4B10208027 4LBWGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P211493

CATALOG NUMBER: LSR4B20D010BZ EC4B10208027 4LBWGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	107	104	110	107	105	103	103	101	99	100	98	96	96	95	94	92																			
2	106	100	96	92	104	99	95	91	95	92	89	92	90	87	90	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	77	76																			
4	94	85	78	74	92	84	78	73	81	76	72	79	75	71	77	74	71	69																			
5	88	78	72	67	86	77	71	66	75	70	66	74	69	65	72	68	64	63																			
6	83	72	65	61	81	71	65	60	70	64	60	68	63	59	67	63	59	57																			
7	78	67	60	55	76	66	60	55	65	59	55	64	58	55	63	58	54	53																			
8	73	62	56	51	72	62	55	51	61	55	50	59	54	50	58	54	50	48																			
9	69	58	51	47	68	58	51	47	57	51	47	56	50	46	55	50	46	45																			
10	65	54	48	43	64	54	48	43	53	47	43	52	47	43	51	46	43	41																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211493

CATALOG NUMBER: LSR4B20D010BZ EC4B10208027 4LBWGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	86.1	6.8
10°-20°	244.0	19.2
20°-30°	349.9	27.6
30°-40°	329.4	26.0
40°-50°	181.9	14.3
50°-60°	58.4	4.6
60°-70°	14.6	1.2
70°-80°	3.5	0.3
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	679.9	53.6
0°-40°	1009.4	79.6
0°-60°	1249.7	98.6
0°-90°	1268.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1268.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	913	
5°	908	86
15°	864	244
25°	768	350
35°	534	329
45°	231	182
55°	59	58
65°	13	15
75°	2	3
85°	0	0
90°	0	



TEST NUMBER: P211493

CATALOG NUMBER: LSR4B20D010BZ EC4B10208027 4LBWGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	912.7
2.5°	906.1
5°	908.3
7.5°	901.7
10°	890.7
12.5°	879.7
15°	864.3
17.5°	851.1
20°	829.1
22.5°	798.3
25°	767.5
27.5°	725.7
30°	670.8
32.5°	609.2
35°	534.4
37.5°	455.2
40°	373.9
42.5°	299.1
45°	230.9
47.5°	173.7
50°	125.4
52.5°	88.0
55°	59.4
57.5°	39.6
60°	28.6
62.5°	19.8
65°	13.2
67.5°	8.8
70°	6.6
72.5°	4.4
75°	2.2
77.5°	2.2
80°	2.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)