

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211645

Luminaire Tested: **LSR4B20D010BZ EC4B10208035 4LBCSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211645
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B20D010BZ EC4B10208035 4LBCSMW1
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH CAST MATTE WHITE TRIM
WATTAGE D010TR-21.86W DE010-20.46W D5LT-21.24W DMX-20.89W DL2-22.5W
DL3-21.8 6W DLE-22.46W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2165.4 lumens
Efficiency: N/A
Efficacy: 104.1 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211645

CATALOG NUMBER: LSR4B20D010BZ EC4B10208035 4LBCSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P211645

CATALOG NUMBER: LSR4B20D010BZ EC4B10208035 4LBCSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	110	106	102	99	108	104	100	97	100	97	94	96	93	91	92	90	89	87																			
2	101	94	87	82	99	92	86	81	88	84	79	85	81	78	82	79	76	74																			
3	93	83	75	70	90	81	74	69	79	73	68	76	71	67	73	69	65	63																			
4	85	74	66	60	83	73	65	59	70	64	58	68	62	58	66	61	57	55																			
5	79	66	58	52	77	65	57	51	63	56	51	61	55	50	60	54	50	48																			
6	73	60	52	45	71	59	51	45	57	50	45	56	49	44	54	49	44	42																			
7	68	55	46	40	66	54	46	40	52	45	40	51	44	40	50	44	39	37																			
8	63	50	42	36	61	49	41	36	48	41	36	47	40	36	46	40	35	33																			
9	59	46	38	33	57	45	38	32	44	37	32	43	37	32	42	36	32	30																			
10	55	42	35	30	54	42	34	30	41	34	29	40	34	29	39	33	29	27																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211645

CATALOG NUMBER: LSR4B20D010BZ EC4B10208035 4LBCSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	83.8	3.9
10°-20°	238.6	11.0
20°-30°	358.9	16.6
30°-40°	425.3	19.6
40°-50°	423.3	19.5
50°-60°	341.2	15.8
60°-70°	206.4	9.5
70°-80°	76.6	3.5
80°-90°	11.4	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	681.3	31.5
0°-40°	1106.6	51.1
0°-60°	1871.0	86.4
0°-90°	2165.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2165.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	884	
5°	880	84
15°	845	239
25°	780	359
35°	681	425
45°	551	423
55°	380	341
65°	207	206
75°	70	77
85°	9	11
90°	0	



TEST NUMBER: P211645

CATALOG NUMBER: LSR4B20D010BZ EC4B10208035 4LBCSMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	884.4
2.5°	884.4
5°	880.5
7.5°	877.9
10°	870.0
12.5°	856.9
15°	845.1
17.5°	832.0
20°	816.2
22.5°	800.5
25°	779.5
27.5°	757.2
30°	732.2
32.5°	708.6
35°	681.1
37.5°	652.2
40°	618.1
42.5°	585.3
45°	551.1
47.5°	513.1
50°	471.1
52.5°	427.8
55°	380.5
57.5°	338.6
60°	291.3
62.5°	249.3
65°	207.3
67.5°	168.0
70°	131.2
72.5°	98.4
75°	69.5
77.5°	44.6
80°	26.2
82.5°	15.7
85°	9.2
87.5°	3.9
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)