

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211742

Luminaire Tested: **LSR4B20D010BZ EC4B10209040 4LBNI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211742
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B20D010BZ EC4B10209040 4LBNI1
Description: PORTFOLIO 4 INCH CYLINDER
NARROW DISTRIBUTION WITH SPECULAR CLEAR TRIM
WATTAGE D010TR-21.86W DE010-20.46W D5LT-21.24W DMX-20.89W DL2-22.5W
DL3-21.8 6W DLE-22.46W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1293.3 lumens
Efficiency: N/A
Efficacy: 62.2 lumens/watt
Spacing Criteria (0/90/45): 0.48 / 0.48 / 0.54
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211742

CATALOG NUMBER: LSR4B20D010BZ EC4B10209040 4LBNLI1

Luminous Intensity Polar Plot





TEST NUMBER: P211742

CATALOG NUMBER: LSR4B20D010BZ EC4B10209040 4LBNLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95																			
2	109	105	102	99	107	103	100	98	100	98	95	97	95	93	95	93	92	90																			
3	105	99	95	92	103	98	94	91	95	92	89	93	90	88	91	89	87	85																			
4	101	94	89	86	99	93	88	85	91	87	84	89	86	83	87	84	82	81																			
5	96	89	84	80	95	88	84	80	87	82	79	85	81	79	83	80	78	77																			
6	92	85	80	76	91	84	79	76	83	78	75	81	78	75	80	77	74	73																			
7	89	81	76	72	88	80	75	72	79	75	71	78	74	71	77	73	71	69																			
8	85	77	72	68	84	77	72	68	76	71	68	75	71	68	74	70	67	66																			
9	82	74	69	65	81	73	68	65	72	68	65	72	68	65	71	67	64	63																			
10	79	71	66	62	78	70	65	62	69	65	62	69	65	62	68	64	62	61																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211742

CATALOG NUMBER: LSR4B20D010BZ EC4B10209040 4LBNLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	262.3	20.3
10°-20°	449.0	34.7
20°-30°	356.9	27.6
30°-40°	188.9	14.6
40°-50°	32.6	2.5
50°-60°	2.4	0.2
60°-70°	1.2	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1068.2	82.6
0°-40°	1257.1	97.2
0°-60°	1292.1	99.9
0°-90°	1293.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1293.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3328	
5°	2984	262
15°	1623	449
25°	769	357
35°	299	189
45°	34	33
55°	2	2
65°	2	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P211742

CATALOG NUMBER: LSR4B20D010BZ EC4B10209040 4LBNLI1

CANDELA DISTRIBUTION (FULL):

	0°
0°	3328.2
2.5°	3242.5
5°	2983.6
7.5°	2645.0
10°	2286.5
12.5°	1939.9
15°	1623.3
17.5°	1328.5
20°	1093.5
22.5°	914.2
25°	768.8
27.5°	651.3
30°	533.8
32.5°	414.3
35°	298.8
37.5°	197.2
40°	117.5
42.5°	67.7
45°	33.9
47.5°	12.0
50°	4.0
52.5°	4.0
55°	2.0
57.5°	2.0
60°	2.0
62.5°	2.0
65°	2.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)