

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211769

Luminaire Tested: **LSR4B20D010BZ EC4B10208050 4LBNGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211769
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B20D010BZ EC4B10208050 4LBNGPH1
Description: PORTFOLIO 4 INCH CYLINDER
NARROW DISTRIBUTION WITH GRAPHITE HAZE TRIM
WATTAGE D010TR-21.86W DE010-20.46W D5LT-21.24W DMX-20.89W DL2-22.5W
DL3-21.8 6W DLE-22.46W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 982.2 lumens
Efficiency: N/A
Efficacy: 47.2 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.88
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211769

CATALOG NUMBER: LSR4B20D010BZ EC4B10208050 4LBNGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P211769

CATALOG NUMBER: LSR4B20D010BZ EC4B10208050 4LBNGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20									
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																			
RCR																																														
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																												
1	114	111	108	106	111	109	106	104	105	103	101	101	100	98	97	96	95	94																												
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	92	91	89	87																												
3	103	96	91	87	101	95	90	87	92	88	85	90	87	84	88	85	83	81																												
4	97	90	84	80	96	89	84	80	87	82	79	85	81	78	83	80	77	76																												
5	93	84	78	74	91	83	78	74	82	77	73	80	76	73	78	75	72	70																												
6	88	79	73	69	86	78	73	69	77	72	68	75	71	68	74	70	67	66																												
7	84	74	68	64	82	74	68	64	72	67	64	71	67	63	70	66	63	62																												
8	80	70	64	60	78	70	64	60	68	63	60	67	63	59	66	62	59	58																												
9	76	66	60	56	75	66	60	56	65	60	56	64	59	56	63	59	56	54																												
10	72	63	57	53	71	62	57	53	61	56	53	61	56	53	60	56	52	51																												

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211769

CATALOG NUMBER: LSR4B20D010BZ EC4B10208050 4LBNGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	107.1	10.9
10°-20°	268.4	27.3
20°-30°	327.2	33.3
30°-40°	215.8	22.0
40°-50°	49.7	5.1
50°-60°	9.5	1.0
60°-70°	3.5	0.4
70°-80°	0.9	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	702.7	71.5
0°-40°	918.6	93.5
0°-60°	977.8	99.5
0°-90°	982.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	982.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1178	
5°	1149	107
15°	961	268
25°	719	327
35°	345	216
45°	55	50
55°	10	10
65°	2	4
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P211769

CATALOG NUMBER: LSR4B20D010BZ EC4B10208050 4LBNGPH1

CANDELA DISTRIBUTION (FULL):

0°	
0°	1177.9
2.5°	1175.5
5°	1149.3
7.5°	1113.6
10°	1066.0
12.5°	1018.5
15°	961.3
17.5°	901.9
20°	840.0
22.5°	785.3
25°	718.6
27.5°	652.0
30°	566.3
32.5°	461.6
35°	345.0
37.5°	240.3
40°	154.7
42.5°	95.2
45°	54.7
47.5°	28.6
50°	16.7
52.5°	14.3
55°	9.5
57.5°	7.1
60°	7.1
62.5°	4.8
65°	2.4
67.5°	2.4
70°	2.4
72.5°	2.4
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)