

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211836

Luminaire Tested: **LSR4B30D010BZ EC4B30509024 4LBSLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211836
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B30D010BZ EC4B30509024 4LBSL11
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH SPECULAR CLEAR TRIM
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W
DL3-29.67W DLE-29.73W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2159.8 lumens
Efficiency: N/A
Efficacy: 77.1 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211836

CATALOG NUMBER: LSR4B30D010BZ EC4B30509024 4LBSLI1

Luminous Intensity Polar Plot





TEST NUMBER: P211836

CATALOG NUMBER: LSR4B30D010BZ EC4B30509024 4LBSLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	112	108	105	102	109	106	103	101	102	100	98	98	96	95	95	93	92	90		
2	104	98	93	88	102	96	91	87	93	89	85	90	86	84	87	84	82	80		
3	97	89	82	77	95	87	81	77	84	79	75	82	78	74	79	76	73	71		
4	90	81	73	68	88	79	73	68	77	71	67	75	70	66	73	69	65	63		
5	84	73	66	61	82	72	65	60	70	64	60	69	63	59	67	62	59	57		
6	79	67	60	54	77	66	59	54	65	58	54	63	58	53	62	57	53	51		
7	74	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46		
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42		
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	44	41	39		
10	61	50	43	38	60	49	42	38	48	42	38	47	42	38	46	41	37	36		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211836

CATALOG NUMBER: LSR4B30D010BZ EC4B30509024 4LBSLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	139.8	6.5
10°-20°	356.6	16.5
20°-30°	462.1	21.4
30°-40°	452.8	21.0
40°-50°	383.8	17.8
50°-60°	251.6	11.6
60°-70°	101.1	4.7
70°-80°	11.6	0.5
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	958.6	44.4
0°-40°	1411.4	65.3
0°-60°	2046.7	94.8
0°-90°	2159.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2159.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1542	
5°	1502	140
15°	1272	357
25°	1009	462
35°	720	453
45°	500	384
55°	280	252
65°	98	101
75°	5	12
85°	0	0
90°	0	



TEST NUMBER: P211836

CATALOG NUMBER: LSR4B30D010BZ EC4B30509024 4LBSLI1

CANDELA DISTRIBUTION (FULL):

	0°
0°	1542.1
2.5°	1530.2
5°	1501.5
7.5°	1453.7
10°	1393.9
12.5°	1329.4
15°	1272.0
17.5°	1209.8
20°	1147.6
22.5°	1080.7
25°	1009.0
27.5°	934.9
30°	858.3
32.5°	786.6
35°	719.7
37.5°	664.7
40°	604.9
42.5°	552.3
45°	499.7
47.5°	444.7
50°	389.7
52.5°	334.7
55°	279.7
57.5°	229.5
60°	181.7
62.5°	138.7
65°	98.0
67.5°	64.6
70°	38.3
72.5°	16.7
75°	4.8
77.5°	2.4
80°	2.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)