

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P212045

Luminaire Tested: **LSR4B30D010BZ EC4B30508035 4LBWH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P212045
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B30D010BZ EC4B30508035 4LBWH1
Description: PORTFOLIO 4 INCH CYLINDER
WIDE DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W
DL3-29.67W DLE-29.73W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2499.8 lumens
Efficiency: N/A
Efficacy: 89.3 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.13
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P212045

CATALOG NUMBER: LSR4B30D010BZ EC4B30508035 4LBWH1

Luminous Intensity Polar Plot





TEST NUMBER: P212045

CATALOG NUMBER: LSR4B30D010BZ EC4B30508035 4LBWH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91			
2	105	100	95	91	103	98	93	90	95	91	88	91	88	86	89	86	84	82			
3	99	91	85	80	97	90	84	80	87	82	78	84	80	77	82	79	76	74			
4	92	83	77	72	90	82	76	71	80	75	70	78	73	70	76	72	69	67			
5	87	77	70	65	85	76	69	64	74	68	64	72	67	63	70	66	62	61			
6	81	71	64	58	80	70	63	58	68	62	58	67	61	57	65	61	57	55			
7	76	65	58	53	75	65	58	53	63	57	53	62	56	52	61	56	52	50			
8	72	60	53	49	70	60	53	49	59	53	48	58	52	48	57	52	48	46			
9	68	56	49	45	66	56	49	45	55	49	44	54	48	44	53	48	44	43			
10	64	52	46	41	63	52	46	41	51	45	41	50	45	41	49	44	41	39			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P212045

CATALOG NUMBER: LSR4B30D010BZ EC4B30508035 4LBWH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	153.4	6.1
10°-20°	442.1	17.7
20°-30°	652.4	26.1
30°-40°	643.9	25.8
40°-50°	394.0	15.8
50°-60°	151.0	6.0
60°-70°	47.2	1.9
70°-80°	13.9	0.6
80°-90°	1.8	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1248.0	49.9
0°-40°	1891.9	75.7
0°-60°	2436.9	97.5
0°-90°	2499.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2499.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1611	
5°	1611	153
15°	1567	442
25°	1428	652
35°	1045	644
45°	505	394
55°	159	151
65°	44	47
75°	14	14
85°	0	2
90°	0	



TEST NUMBER: P212045

CATALOG NUMBER: LSR4B30D010BZ EC4B30508035 4LBWH1

CANDELA DISTRIBUTION (FULL):

0°	
0°	1611.3
2.5°	1614.7
5°	1611.3
7.5°	1607.9
10°	1597.7
12.5°	1584.1
15°	1567.2
17.5°	1546.8
20°	1516.3
22.5°	1482.4
25°	1428.1
27.5°	1360.2
30°	1275.4
32.5°	1170.3
35°	1044.8
37.5°	905.7
40°	763.2
42.5°	630.9
45°	505.4
47.5°	393.5
50°	298.5
52.5°	220.5
55°	159.4
57.5°	111.9
60°	81.4
62.5°	61.1
65°	44.1
67.5°	33.9
70°	23.7
72.5°	17.0
75°	13.6
77.5°	6.8
80°	6.8
82.5°	3.4
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)