

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P212207

Luminaire Tested: **LSR4B40D010BZ EC4B30509024 4LBNMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P212207
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B40D010BZ EC4B30509024 4LBNMW1
Description: PORTFOLIO 4 INCH CYLINDER
NARROW DISTRIBUTION WITH MATTE WHITE TRIM
WATTAGE D010TR-43.02W DE010-42.54W D5LT-42.539W DMX-41.87W DL2-41.57W
DL3-44.71W DLE-39.33W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2107.2 lumens
Efficiency: N/A
Efficacy: 50.4 lumens/watt
Spacing Criteria (0/90/45): 0.96 / 0.96 / 0.95
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P212207

CATALOG NUMBER: LSR4B40D010BZ EC4B30509024 4LBNMW1

Luminous Intensity Polar Plot





TEST NUMBER: P212207

CATALOG NUMBER: LSR4B40D010BZ EC4B30509024 4LBNMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	112	109	105	103	109	106	104	101	102	100	98	98	97	95	95	94	92	90		
2	105	99	94	90	103	97	93	89	94	90	87	91	88	85	88	85	83	81		
3	98	90	84	80	96	89	83	79	86	82	78	84	80	76	81	78	75	73		
4	92	83	76	71	90	82	76	71	80	74	70	78	73	69	76	72	68	67		
5	87	77	70	65	85	76	69	64	74	68	64	72	67	63	70	66	63	61		
6	82	71	64	59	80	70	64	59	69	63	58	67	62	58	66	61	58	56		
7	77	66	59	54	75	65	59	54	64	58	54	63	57	53	62	57	53	52		
8	73	62	55	50	71	61	55	50	60	54	50	59	53	49	58	53	49	48		
9	69	58	51	46	68	57	51	46	56	50	46	55	50	46	54	49	46	44		
10	65	54	48	43	64	54	47	43	53	47	43	52	47	43	51	46	43	41		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P212207

CATALOG NUMBER: LSR4B40D010BZ EC4B30509024 4LBNMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	165.4	7.8
10°-20°	432.7	20.5
20°-30°	569.5	27.0
30°-40°	443.3	21.0
40°-50°	215.3	10.2
50°-60°	136.0	6.5
60°-70°	87.7	4.2
70°-80°	45.9	2.2
80°-90°	11.3	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1167.6	55.4
0°-40°	1610.9	76.4
0°-60°	1962.2	93.1
0°-90°	2107.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2107.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1798	
5°	1764	165
15°	1543	433
25°	1255	569
35°	710	443
45°	268	215
55°	151	136
65°	87	88
75°	44	46
85°	10	11
90°	0	



TEST NUMBER: P212207

CATALOG NUMBER: LSR4B40D010BZ EC4B30509024 4LBNMW1

CANDELA DISTRIBUTION (FULL):

0°	
0°	1797.6
2.5°	1787.6
5°	1764.2
7.5°	1724.0
10°	1670.4
12.5°	1610.2
15°	1543.2
17.5°	1472.9
20°	1399.3
22.5°	1329.0
25°	1255.3
27.5°	1161.6
30°	1034.4
32.5°	883.8
35°	709.7
37.5°	549.0
40°	425.1
42.5°	331.4
45°	267.8
47.5°	217.6
50°	190.8
52.5°	170.7
55°	150.6
57.5°	133.9
60°	117.2
62.5°	100.4
65°	87.0
67.5°	77.0
70°	63.6
72.5°	53.6
75°	43.5
77.5°	33.5
80°	23.4
82.5°	16.7
85°	10.0
87.5°	3.3
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)