

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P212214

Luminaire Tested: **LSR4B40D010BZ EC4B30509024 4LBSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P212214
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B40D010BZ EC4B30509024 4LBSMW1
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH MATTE WHITE TRIM
WATTAGE D010TR-43.02W DE010-42.54W D5LT-42.539W DMX-41.87W DL2-41.57W
DL3-44.71W DLE-39.33W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3025.2 lumens
Efficiency: N/A
Efficacy: 72.4 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P212214

CATALOG NUMBER: LSR4B40D010BZ EC4B30509024 4LBSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P212214

CATALOG NUMBER: LSR4B40D010BZ EC4B30509024 4LBSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	110	106	102	99	107	104	100	97	99	97	94	96	93	91	92	90	88	86																			
2	101	93	87	82	98	92	86	81	88	83	79	85	81	77	82	79	76	74																			
3	93	83	75	69	90	81	74	69	78	72	67	76	70	66	73	69	65	63																			
4	85	74	65	59	83	72	65	59	70	63	58	68	62	57	66	61	56	54																			
5	78	66	58	51	76	65	57	51	63	56	51	61	55	50	59	54	49	47																			
6	73	60	51	45	71	59	51	45	57	50	44	55	49	44	54	48	44	42																			
7	67	54	46	40	66	54	46	40	52	45	40	51	44	39	49	43	39	37																			
8	63	50	41	36	61	49	41	36	48	41	35	46	40	35	45	39	35	33																			
9	59	46	38	32	57	45	37	32	44	37	32	43	36	32	42	36	32	30																			
10	55	42	34	29	54	42	34	29	41	34	29	40	33	29	39	33	29	27																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P212214

CATALOG NUMBER: LSR4B40D010BZ EC4B30509024 4LBSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	115.5	3.8
10°-20°	329.2	10.9
20°-30°	495.8	16.4
30°-40°	589.9	19.5
40°-50°	588.9	19.5
50°-60°	478.9	15.8
60°-70°	294.6	9.7
70°-80°	114.1	3.8
80°-90°	18.3	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	940.5	31.1
0°-40°	1530.4	50.6
0°-60°	2598.2	85.9
0°-90°	3025.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3025.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1219	
5°	1215	115
15°	1169	329
25°	1079	496
35°	945	590
45°	765	589
55°	536	479
65°	296	295
75°	104	114
85°	14	18
90°	0	



TEST NUMBER: P212214

CATALOG NUMBER: LSR4B40D010BZ EC4B30509024 4LBSMW1

CANDELA DISTRIBUTION (FULL):

0°	
0°	1218.9
2.5°	1220.7
5°	1215.3
7.5°	1208.1
10°	1199.1
12.5°	1183.0
15°	1168.7
17.5°	1147.2
20°	1123.9
22.5°	1102.3
25°	1079.0
27.5°	1046.8
30°	1014.5
32.5°	984.0
35°	944.6
37.5°	901.6
40°	862.2
42.5°	813.8
45°	765.4
47.5°	713.4
50°	657.8
52.5°	600.5
55°	535.9
57.5°	473.2
60°	412.3
62.5°	353.1
65°	295.8
67.5°	242.0
70°	191.8
72.5°	145.2
75°	104.0
77.5°	68.1
80°	41.2
82.5°	25.1
85°	14.3
87.5°	7.2
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)