

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P212271

Luminaire Tested: **LSR4B40D010BZ EC4B30509027 4LBSLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P212271
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B40D010BZ EC4B30509027 4LBSLI1
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH SPECULAR CLEAR TRIM
WATTAGE D010TR-43.02W DE010-42.54W D5LT-42.539W DMX-41.87W DL2-41.57W
DL3-44.71W DLE-39.33W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3438.7 lumens
Efficiency: N/A
Efficacy: 82.3 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P212271

CATALOG NUMBER: LSR4B40D010BZ EC4B30509027 4LBSLI1

Luminous Intensity Polar Plot





TEST NUMBER: P212271

CATALOG NUMBER: LSR4B40D010BZ EC4B30509027 4LBSLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	112	108	105	102	109	106	103	101	102	100	98	98	96	95	95	93	92	90		
2	104	98	93	88	102	96	91	87	93	89	85	90	86	84	87	84	82	80		
3	97	89	82	77	95	87	81	77	84	79	75	82	78	74	79	76	73	71		
4	90	81	73	68	88	79	73	68	77	71	67	75	70	66	73	69	65	63		
5	84	73	66	61	82	72	65	60	70	64	60	69	63	59	67	62	59	57		
6	79	67	60	54	77	66	59	54	65	58	54	63	58	53	62	57	53	51		
7	74	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46		
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42		
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	44	41	39		
10	61	50	43	38	60	49	42	38	48	42	38	47	42	38	46	41	37	36		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P212271

CATALOG NUMBER: LSR4B40D010BZ EC4B30509027 4LBSLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	222.6	6.5
10°-20°	567.8	16.5
20°-30°	735.7	21.4
30°-40°	720.9	21.0
40°-50°	611.1	17.8
50°-60°	400.6	11.6
60°-70°	161.0	4.7
70°-80°	18.4	0.5
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1526.2	44.4
0°-40°	2247.1	65.3
0°-60°	3258.7	94.8
0°-90°	3438.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3438.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2455	
5°	2391	223
15°	2025	568
25°	1606	736
35°	1146	721
45°	796	611
55°	445	401
65°	156	161
75°	8	18
85°	0	1
90°	0	



TEST NUMBER: P212271

CATALOG NUMBER: LSR4B40D010BZ EC4B30509027 4LBSLI1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2455.3
2.5°	2436.3
5°	2390.6
7.5°	2314.5
10°	2219.3
12.5°	2116.5
15°	2025.2
17.5°	1926.2
20°	1827.2
22.5°	1720.6
25°	1606.4
27.5°	1488.4
30°	1366.6
32.5°	1252.4
35°	1145.8
37.5°	1058.3
40°	963.1
42.5°	879.4
45°	795.6
47.5°	708.1
50°	620.5
52.5°	532.9
55°	445.4
57.5°	365.4
60°	289.3
62.5°	220.8
65°	156.1
67.5°	102.8
70°	60.9
72.5°	26.6
75°	7.6
77.5°	3.8
80°	3.8
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)