

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P212358

Luminaire Tested: **LSR4B40D010BZ EC4B30509030 4LBSLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P212358
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B40D010BZ EC4B30509030 4LBSLI1
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH SPECULAR CLEAR TRIM
WATTAGE D010TR-43.02W DE010-42.54W D5LT-42.539W DMX-41.87W DL2-41.57W
DL3-44.71W DLE-39.33W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3575.4 lumens
Efficiency: N/A
Efficacy: 85.5 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P212358

CATALOG NUMBER: LSR4B40D010BZ EC4B30509030 4LBSLI1

Luminous Intensity Polar Plot





TEST NUMBER: P212358

CATALOG NUMBER: LSR4B40D010BZ EC4B30509030 4LBSLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	108	105	102	109	106	103	101	102	100	98	98	96	95	95	93	92	90			
2	104	98	93	88	102	96	91	87	93	89	85	90	86	84	87	84	82	80			
3	97	89	82	77	95	87	81	77	84	79	75	82	78	74	79	76	73	71			
4	90	81	73	68	88	79	73	68	77	71	67	75	70	66	73	69	65	63			
5	84	73	66	61	82	72	65	60	70	64	60	69	63	59	67	62	59	57			
6	79	67	60	54	77	66	59	54	65	58	54	63	58	53	62	57	53	51			
7	74	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46			
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42			
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	44	41	39			
10	61	50	43	38	60	49	42	38	48	42	38	47	42	38	46	41	37	36			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P212358

CATALOG NUMBER: LSR4B40D010BZ EC4B30509030 4LBSLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	231.5	6.5
10°-20°	590.4	16.5
20°-30°	765.0	21.4
30°-40°	749.6	21.0
40°-50°	635.3	17.8
50°-60°	416.5	11.6
60°-70°	167.4	4.7
70°-80°	19.2	0.5
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1586.8	44.4
0°-40°	2336.4	65.3
0°-60°	3388.2	94.8
0°-90°	3575.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3575.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2553	
5°	2486	231
15°	2106	590
25°	1670	765
35°	1191	750
45°	827	635
55°	463	416
65°	162	167
75°	8	19
85°	0	1
90°	0	



TEST NUMBER: P212358

CATALOG NUMBER: LSR4B40D010BZ EC4B30509030 4LBSLI1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2552.9
2.5°	2533.1
5°	2485.6
7.5°	2406.4
10°	2307.5
12.5°	2200.6
15°	2105.6
17.5°	2002.7
20°	1899.8
22.5°	1789.0
25°	1670.3
27.5°	1547.6
30°	1420.9
32.5°	1302.2
35°	1191.3
37.5°	1100.3
40°	1001.4
42.5°	914.3
45°	827.2
47.5°	736.2
50°	645.1
52.5°	554.1
55°	463.1
57.5°	380.0
60°	300.8
62.5°	229.6
65°	162.3
67.5°	106.9
70°	63.3
72.5°	27.7
75°	7.9
77.5°	4.0
80°	4.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)