

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P212441

Luminaire Tested: **LSR4B40D010BZ EC4B30509035 4LBPSMW1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P212441  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR4B40D010BZ EC4B30509035 4LBPSMW1  
Description: PORTFOLIO 4 INCH CYLINDER  
SHALLOW DISTRIBUTION WITH PLASTIC MATTE WHITE TRIM  
WATTAGE D010TR-43.02W DE010-42.54W D5LT-42.539W DMX-41.87W DL2-41.57W  
DL3-44.71W DLE-39.33W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 3775.2 lumens  
Efficiency: N/A  
Efficacy: 90.3 lumens/watt  
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 41.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P212441

CATALOG NUMBER: LSR4B40D010BZ EC4B30509035 4LBPSMW1

### Luminous Intensity Polar Plot





TEST NUMBER: P212441

CATALOG NUMBER: LSR4B40D010BZ EC4B30509035 4LBPSMW1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	110	106	102	99	107	104	100	97	99	97	94	96	93	91	92	90	88	86	86	86	86
2	101	93	87	82	98	92	86	81	88	83	79	85	81	77	82	79	76	74	74	74	74
3	93	83	75	69	90	81	74	69	78	72	67	76	70	66	73	69	65	63	63	63	63
4	85	74	66	59	83	72	65	59	70	63	58	68	62	57	66	61	56	54	54	54	54
5	78	66	58	51	76	65	57	51	63	56	51	61	55	50	59	54	49	47	47	47	47
6	73	60	51	45	71	59	51	45	57	50	44	55	49	44	54	48	44	42	42	42	42
7	67	54	46	40	66	54	46	40	52	45	40	51	44	39	49	43	39	37	37	37	37
8	63	50	41	36	61	49	41	36	48	41	35	46	40	35	45	39	35	33	33	33	33
9	59	46	38	32	57	45	37	32	44	37	32	43	36	32	42	36	32	30	30	30	30
10	55	42	34	29	54	42	34	29	41	34	29	40	33	29	39	33	29	27	27	27	27

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P212441

CATALOG NUMBER: LSR4B40D010BZ EC4B30509035 4LBPSMW1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	144.1	3.8
10°-20°	410.8	10.9
20°-30°	618.7	16.4
30°-40°	736.2	19.5
40°-50°	734.9	19.5
50°-60°	597.6	15.8
60°-70°	367.7	9.7
70°-80°	142.4	3.8
80°-90°	22.8	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1173.7	31.1
0°-40°	1909.8	50.6
0°-60°	3242.3	85.9
0°-90°	3775.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3775.2	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1521	
5°	1517	144
15°	1458	411
25°	1347	619
35°	1179	736
45°	955	735
55°	669	598
65°	369	368
75°	130	142
85°	18	23
90°	0	



TEST NUMBER: P212441

CATALOG NUMBER: LSR4B40D010BZ EC4B30509035 4LBPSMW1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1521.1
2.5°	1523.3
5°	1516.6
7.5°	1507.6
10°	1496.5
12.5°	1476.3
15°	1458.4
17.5°	1431.6
20°	1402.5
22.5°	1375.7
25°	1346.6
27.5°	1306.3
30°	1266.1
32.5°	1228.0
35°	1178.8
37.5°	1125.1
40°	1075.9
42.5°	1015.5
45°	955.1
47.5°	890.3
50°	820.9
52.5°	749.3
55°	668.8
57.5°	590.5
60°	514.5
62.5°	440.7
65°	369.1
67.5°	302.0
70°	239.3
72.5°	181.2
75°	129.7
77.5°	85.0
80°	51.4
82.5°	31.3
85°	17.9
87.5°	8.9
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)