

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P212557

Luminaire Tested: **LSR4B40D010BZ EC4B30509050 4LBPSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P212557
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B40D010BZ EC4B30509050 4LBPSMW1
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH PLASTIC MATTE WHITE TRIM
WATTAGE D010TR-43.02W DE010-42.54W D5LT-42.539W DMX-41.87W DL2-41.57W
DL3-44.71W DLE-39.33W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3798.1 lumens
Efficiency: N/A
Efficacy: 90.9 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P212557

CATALOG NUMBER: LSR4B40D010BZ EC4B30509050 4LBPSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P212557

CATALOG NUMBER: LSR4B40D010BZ EC4B30509050 4LBPSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	110	106	102	99	107	104	100	97	99	97	94	96	93	91	92	90	88	86																			
2	101	93	87	82	98	92	86	81	88	83	79	85	81	77	82	79	76	74																			
3	93	83	75	69	90	81	74	69	78	72	67	76	70	66	73	69	65	63																			
4	85	74	66	59	83	72	65	59	70	63	58	68	62	57	66	61	56	54																			
5	78	66	58	51	76	65	57	51	63	56	51	61	55	50	59	54	49	47																			
6	73	60	51	45	71	59	51	45	57	50	44	55	49	44	54	48	44	42																			
7	67	54	46	40	66	54	46	40	52	45	40	51	44	39	49	43	39	37																			
8	63	50	41	36	61	49	41	36	48	41	35	46	40	35	45	39	35	33																			
9	59	46	38	32	57	45	37	32	44	37	32	43	36	32	42	36	32	30																			
10	55	42	34	29	54	42	34	29	41	34	29	40	33	29	39	33	29	27																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P212557

CATALOG NUMBER: LSR4B40D010BZ EC4B30509050 4LBPSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	145.0	3.8
10°-20°	413.3	10.9
20°-30°	622.4	16.4
30°-40°	740.7	19.5
40°-50°	739.3	19.5
50°-60°	601.3	15.8
60°-70°	369.9	9.7
70°-80°	143.3	3.8
80°-90°	23.0	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1180.8	31.1
0°-40°	1921.4	50.6
0°-60°	3262.0	85.9
0°-90°	3798.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3798.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1530	
5°	1526	145
15°	1467	413
25°	1355	622
35°	1186	741
45°	961	739
55°	673	601
65°	371	370
75°	130	143
85°	18	23
90°	0	



TEST NUMBER: P212557

CATALOG NUMBER: LSR4B40D010BZ EC4B30509050 4LBPSMW1

CANDELA DISTRIBUTION (FULL):

0°	
0°	1530.3
2.5°	1532.5
5°	1525.8
7.5°	1516.8
10°	1505.5
12.5°	1485.3
15°	1467.3
17.5°	1440.3
20°	1411.0
22.5°	1384.0
25°	1354.7
27.5°	1314.2
30°	1273.7
32.5°	1235.5
35°	1186.0
37.5°	1131.9
40°	1082.4
42.5°	1021.7
45°	960.9
47.5°	895.7
50°	825.9
52.5°	753.9
55°	672.9
57.5°	594.1
60°	517.6
62.5°	443.3
65°	371.3
67.5°	303.8
70°	240.8
72.5°	182.3
75°	130.5
77.5°	85.5
80°	51.8
82.5°	31.5
85°	18.0
87.5°	9.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)