

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P843436

Luminaire Tested: **LD4C20DE010B2750 EU4C20B30 4LBCSMB**

Issue Date: 5/7/2024



Test Information

Test Method: LM-79-08
Report Number: P843436
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P206301)
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2024
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C20DE010B2750 EU4C20B30 4LBCSMB
Description: 4in Downlight with BioUp LEDs
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1292.4 lumens
Efficiency: N/A
Efficacy: 59.3 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 21.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P843436

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBCSMB

Luminous Intensity Polar Plot





TEST NUMBER: P843436

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBCSMB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	110	106	102	99	108	104	100	97	100	97	94	96	93	91	92	90	89	87				87
2	101	94	87	82	99	92	86	81	88	84	79	85	81	78	82	79	76	74				74
3	93	83	75	70	90	81	74	69	79	73	68	76	71	67	73	69	65	63				63
4	85	74	66	60	83	73	65	59	70	64	58	68	62	58	66	61	57	55				55
5	79	66	58	52	77	65	57	51	63	56	51	61	55	50	60	54	50	48				48
6	73	60	52	45	71	59	51	45	57	50	45	56	49	44	54	49	44	42				42
7	68	55	46	40	66	54	46	40	52	45	40	51	44	40	50	44	39	37				37
8	63	50	42	36	61	49	41	36	48	41	36	47	40	36	46	40	35	33				33
9	59	46	38	33	57	45	38	32	44	37	32	43	37	32	42	36	32	30				30
10	55	42	35	30	54	42	34	30	41	34	29	40	34	29	39	33	29	27				27

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	64854
5°	64806
10°	64782
15°	64153
20°	63682
25°	63073
30°	61992
35°	60980
40°	59162
45°	57143
50°	53745
55°	48642
60°	42728
65°	35959
70°	28125
75°	19699
80°	11108
85°	7612



TEST NUMBER: P843436

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBCSMB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	50.0	3.9
10°-20°	142.4	11.0
20°-30°	214.2	16.6
30°-40°	253.9	19.6
40°-50°	252.6	19.5
50°-60°	203.6	15.8
60°-70°	123.2	9.5
70°-80°	45.7	3.5
80°-90°	6.8	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	406.6	31.5
0°-40°	660.5	51.1
0°-60°	1116.7	86.4
0°-90°	1292.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1292.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	528	
5°	526	50
15°	504	142
25°	465	214
35°	407	254
45°	329	253
55°	227	204
65°	124	123
75°	42	46
85°	5	7
90°	0	



TEST NUMBER: P843436

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBCSMB

CANDELA DISTRIBUTION (FULL):

	0°
0°	527.9
2.5°	527.9
5°	525.5
7.5°	524.0
10°	519.3
12.5°	511.5
15°	504.4
17.5°	496.6
20°	487.1
22.5°	477.8
25°	465.3
27.5°	451.8
30°	437.0
32.5°	422.9
35°	406.6
37.5°	389.3
40°	368.9
42.5°	349.3
45°	328.9
47.5°	306.2
50°	281.2
52.5°	255.3
55°	227.1
57.5°	202.1
60°	173.9
62.5°	148.8
65°	123.7
67.5°	100.3
70°	78.3
72.5°	58.7
75°	41.5
77.5°	26.7
80°	15.7
82.5°	9.4
85°	5.4
87.5°	2.3
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)