

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P843437

Luminaire Tested: **LD4C20DE010B2750 EU4C20B30 4LBCSMMS**

Issue Date: 5/7/2024



Test Information

Test Method: LM-79-08
Report Number: P843437
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P206301)
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2024
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C20DE010B2750 EU4C20B30 4LBSCMMS
Description: 4in Downlight with BioUp LEDs
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1321.0 lumens
Efficiency: N/A
Efficacy: 60.6 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 21.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P843437

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBCSMMS

Luminous Intensity Polar Plot





TEST NUMBER: P843437

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBSCMMS

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	110	106	102	99	108	104	100	97	100	97	94	96	93	91	92	90	89	87				87
2	101	94	87	82	99	92	86	81	88	84	79	85	81	78	82	79	76	74				74
3	93	83	75	70	90	81	74	69	79	73	68	76	71	67	73	69	65	63				63
4	85	74	66	60	83	73	65	59	70	64	58	68	62	58	66	61	57	55				55
5	79	66	58	52	77	65	57	51	63	56	51	61	55	50	60	54	50	48				48
6	73	60	52	45	71	59	51	45	57	50	45	56	49	44	54	49	44	42				42
7	68	55	46	40	66	54	46	40	52	45	40	51	44	40	50	44	39	37				37
8	63	50	42	36	61	49	41	36	48	41	36	47	40	36	46	40	35	33				33
9	59	46	38	33	57	45	38	32	44	37	32	43	37	32	42	36	32	30				30
10	55	42	35	30	54	42	34	30	41	34	29	40	34	29	39	33	29	27				27

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	66279
5°	66249
10°	66204
15°	65578
20°	65094
25°	64456
30°	63354
35°	62315
40°	60461
45°	58412
50°	54949
55°	49692
60°	43687
65°	36773
70°	28736
75°	20126
80°	11391
85°	7753



TEST NUMBER: P843437

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBCSMMS

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	51.1	3.9
10°-20°	145.5	11.0
20°-30°	218.9	16.6
30°-40°	259.5	19.6
40°-50°	258.2	19.5
50°-60°	208.1	15.8
60°-70°	125.9	9.5
70°-80°	46.8	3.5
80°-90°	6.9	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	415.6	31.5
0°-40°	675.0	51.1
0°-60°	1141.4	86.4
0°-90°	1321.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1321.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	540	
5°	537	51
15°	516	146
25°	476	219
35°	416	259
45°	336	258
55°	232	208
65°	126	126
75°	42	47
85°	6	7
90°	0	



TEST NUMBER: P843437

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBCSMMS

CANDELA DISTRIBUTION (FULL):

	0°
0°	539.5
2.5°	539.5
5°	537.2
7.5°	535.6
10°	530.7
12.5°	522.7
15°	515.6
17.5°	507.6
20°	497.9
22.5°	488.3
25°	475.5
27.5°	461.9
30°	446.6
32.5°	432.3
35°	415.5
37.5°	397.9
40°	377.0
42.5°	357.1
45°	336.2
47.5°	313.0
50°	287.5
52.5°	260.9
55°	232.0
57.5°	206.6
60°	177.8
62.5°	152.1
65°	126.5
67.5°	102.4
70°	80.0
72.5°	60.1
75°	42.4
77.5°	27.3
80°	16.1
82.5°	9.6
85°	5.5
87.5°	2.3
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)