

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P843438

Luminaire Tested: **LD4C20DE010B2750 EU4C20B30 4LBCSMW**

Issue Date: 5/7/2024



Test Information

Test Method: LM-79-08
Report Number: P843438
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P206301)
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2024
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C20DE010B2750 EU4C20B30 4LBSCMW
Description: 4in Downlight with BioUp LEDs
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1615.0 lumens
Efficiency: N/A
Efficacy: 74.1 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 21.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P843438

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBCSMW

Luminous Intensity Polar Plot





TEST NUMBER: P843438

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBSCMW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	110	106	102	99	108	104	100	97	100	97	94	96	93	91	92	90	89	87				87
2	101	94	87	82	99	92	86	81	88	84	79	85	81	78	82	79	76	74				74
3	93	83	75	70	90	81	74	69	79	73	68	76	71	67	73	69	65	63				63
4	85	74	66	60	83	73	65	59	70	64	58	68	62	58	66	61	57	55				55
5	79	66	58	52	77	65	57	51	63	56	51	61	55	50	60	54	50	48				48
6	73	60	52	45	71	59	51	45	57	50	45	56	49	44	54	49	44	42				42
7	68	55	46	40	66	54	46	40	52	45	40	51	44	40	50	44	39	37				37
8	63	50	42	36	61	49	41	36	48	41	36	47	40	36	46	40	35	33				33
9	59	46	38	33	57	45	38	32	44	37	32	43	37	32	42	36	32	30				30
10	55	42	35	30	54	42	34	30	41	34	29	40	34	29	39	33	29	27				27

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	81022
5°	80986
10°	80949
15°	80166
20°	79593
25°	78811
30°	77469
35°	76188
40°	73916
45°	71425
50°	67181
55°	60787
60°	53392
65°	44942
70°	35130
75°	24588
80°	13867
85°	9585



TEST NUMBER: P843438

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBCSMW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	62.5	3.9
10°-20°	177.9	11.0
20°-30°	267.7	16.6
30°-40°	317.2	19.6
40°-50°	315.7	19.5
50°-60°	254.5	15.8
60°-70°	153.9	9.5
70°-80°	57.1	3.5
80°-90°	8.5	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	508.1	31.5
0°-40°	825.3	51.1
0°-60°	1395.5	86.4
0°-90°	1615.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1615.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	660	
5°	657	62
15°	630	178
25°	581	268
35°	508	317
45°	411	316
55°	284	255
65°	155	154
75°	52	57
85°	7	8
90°	0	



TEST NUMBER: P843438

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBCSMW

CANDELA DISTRIBUTION (FULL):

	0°
0°	659.5
2.5°	659.5
5°	656.7
7.5°	654.8
10°	648.9
12.5°	639.1
15°	630.3
17.5°	620.5
20°	608.8
22.5°	597.0
25°	581.4
27.5°	564.7
30°	546.1
32.5°	528.5
35°	508.0
37.5°	486.4
40°	460.9
42.5°	436.6
45°	411.1
47.5°	382.7
50°	351.5
52.5°	319.0
55°	283.8
57.5°	252.6
60°	217.3
62.5°	185.9
65°	154.6
67.5°	125.2
70°	97.8
72.5°	73.4
75°	51.8
77.5°	33.3
80°	19.6
82.5°	11.7
85°	6.8
87.5°	2.9
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)