

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P843449

Luminaire Tested: **LD4C20DE010B2750 EU4C20B30 4LBWLI**

Issue Date: 2/17/2023



Test Information

Test Method: LM-79-08
Report Number: P843449
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208077)
Test Lab: INNOVATION CENTER
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C20DE010B2750 EU4C20B30 4LBWLI
Description: 4in Downlight with BioUp LEDs
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1851.8 lumens
Efficiency: N/A
Efficacy: 84.9 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.18
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 21.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P843449

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBWLI

Luminous Intensity Polar Plot





TEST NUMBER: P843449

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBWLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92	92	92	92
2	106	101	97	93	104	99	95	92	96	93	90	93	90	88	90	88	86	84	84	84	84
3	100	93	87	83	98	92	86	82	89	85	81	86	83	80	84	81	78	77	77	77	77
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	72	70	70	70	70
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64	64	64	64
6	83	73	66	62	82	72	66	61	71	65	61	69	64	60	68	63	60	58	58	58	58
7	78	68	61	56	77	67	61	56	66	60	56	64	59	55	63	59	55	54	54	54	54
8	74	63	56	52	72	62	56	51	61	55	51	60	55	51	59	54	51	49	49	49	49
9	69	59	52	48	68	58	52	47	57	51	47	56	51	47	55	50	47	45	45	45	45
10	66	55	48	44	65	54	48	44	53	48	44	53	47	44	52	47	43	42	42	42	42

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	139390
5°	141760
10°	148164
15°	157267
20°	164155
25°	162732
30°	151335
35°	129460
40°	98630
45°	57856
50°	24713
55°	7282
60°	2089
65°	1221
70°	754
75°	997
80°	0
85°	0



TEST NUMBER: P843449

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBWLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	111.0	6.0
10°-20°	350.2	18.9
20°-30°	546.3	29.5
30°-40°	531.5	28.7
40°-50°	265.5	14.3
50°-60°	41.1	2.2
60°-70°	4.9	0.3
70°-80°	1.4	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1007.4	54.4
0°-40°	1538.9	83.1
0°-60°	1845.5	99.7
0°-90°	1851.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1851.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1135	
5°	1150	111
15°	1236	350
25°	1200	546
35°	863	532
45°	333	265
55°	34	41
65°	4	5
75°	2	1
85°	0	0
90°	0	



TEST NUMBER: P843449

CATALOG NUMBER: LD4C20DE010B2750 EU4C20B30 4LBWLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	1134.6
2.5°	1138.9
5°	1149.5
7.5°	1166.5
10°	1187.7
12.5°	1215.2
15°	1236.5
17.5°	1253.5
20°	1255.6
22.5°	1240.7
25°	1200.5
27.5°	1141.1
30°	1066.8
32.5°	973.6
35°	863.2
37.5°	742.2
40°	615.0
42.5°	479.3
45°	333.0
47.5°	214.2
50°	129.3
52.5°	70.0
55°	34.0
57.5°	14.9
60°	8.5
62.5°	6.3
65°	4.2
67.5°	4.2
70°	2.1
72.5°	2.1
75°	2.1
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)