

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P843317

Luminaire Tested: **LD4C10DE010B35 EU4C10B35 4LBMLI**

Issue Date: 2/17/2023



Test Information

Test Method: LM-79-08
Report Number: P843317
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208178)
Test Lab: INNOVATION CENTER
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C10DE010B35 EU4C10B35 4LBMLI
Description: 4in Downlight with BioUp LEDs
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1101.0 lumens
Efficiency: N/A
Efficacy: 82.8 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.76
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 13.3
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P843317

CATALOG NUMBER: LD4C10DE010B35 EU4C10B35 4LBMLI

Luminous Intensity Polar Plot





TEST NUMBER: P843317

CATALOG NUMBER: LD4C10DE010B35 EU4C10B35 4LBMLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94			
2	109	104	100	97	107	102	99	96	99	96	94	96	94	92	94	92	90	88			
3	104	98	93	89	102	96	92	89	94	90	87	91	88	86	89	87	85	83			
4	99	92	87	83	97	91	86	82	89	85	81	87	83	80	85	82	79	78			
5	94	87	81	77	93	86	81	77	84	79	76	82	78	75	81	77	75	73			
6	90	82	76	72	89	81	76	72	80	75	71	78	74	71	77	73	70	69			
7	86	77	72	68	85	77	71	68	75	71	67	74	70	67	73	69	67	65			
8	82	73	68	64	81	73	67	64	72	67	64	71	66	63	70	66	63	62			
9	79	70	64	60	78	69	64	60	68	63	60	67	63	60	67	63	60	58			
10	75	66	61	57	74	66	61	57	65	60	57	64	60	57	64	60	57	56			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	213237
5°	209599
10°	192587
15°	161286
20°	129221
25°	103821
30°	77285
35°	44153
40°	20720
45°	8809
50°	2810
55°	1435
60°	983
65°	756
70°	503
75°	0
80°	0
85°	0



TEST NUMBER: P843317

CATALOG NUMBER: LD4C10DE010B35 EU4C10B35 4LBMLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	157.2	14.3
10°-20°	351.3	31.9
20°-30°	349.3	31.7
30°-40°	190.2	17.3
40°-50°	44.0	4.0
50°-60°	6.2	0.6
60°-70°	2.3	0.2
70°-80°	0.5	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	857.8	77.9
0°-40°	1048.0	95.2
0°-60°	1098.2	99.7
0°-90°	1101.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1101.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1736	
5°	1700	157
15°	1268	351
25°	766	349
35°	294	190
45°	51	44
55°	7	6
65°	3	2
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P843317

CATALOG NUMBER: LD4C10DE010B35 EU4C10B35 4LBMLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	1735.7
2.5°	1731.7
5°	1699.6
7.5°	1634.5
10°	1543.8
12.5°	1410.7
15°	1268.1
17.5°	1126.9
20°	988.4
22.5°	875.2
25°	765.9
27.5°	662.1
30°	544.8
32.5°	414.3
35°	294.4
37.5°	198.4
40°	129.2
42.5°	81.2
45°	50.7
47.5°	29.3
50°	14.7
52.5°	8.0
55°	6.7
57.5°	4.0
60°	4.0
62.5°	2.6
65°	2.6
67.5°	1.4
70°	1.4
72.5°	1.4
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)