

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P843246

Luminaire Tested: **LD4C08DE010B35 EU4C08B35 4LBMH**

Issue Date: 2/17/2023



**Test Information**

Test Method: LM-79-08  
Report Number: P843246  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)  
Test Lab: INNOVATION CENTER  
Issue Date: 2/17/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD4C08DE010B35 EU4C08B35 4LBMH  
Description: 4in Downlight with BioUp LEDs  
Light Source: -  
Ballast/Driver:

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 618.8 lumens  
Efficiency: N/A  
Efficacy: 64.5 lumens/watt  
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct

Input Watts (W): 9.6  
Input Voltage (V):  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P843246

CATALOG NUMBER: LD4C08DE010B35 EU4C08B35 4LBMH

### Luminous Intensity Polar Plot





TEST NUMBER: P843246

CATALOG NUMBER: LD4C08DE010B35 EU4C08B35 4LBMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93				93
2	107	102	98	94	105	100	96	93	97	94	91	94	91	89	91	89	87	85				85
3	101	94	89	85	99	93	88	84	90	86	83	88	84	82	86	83	80	79				79
4	96	88	82	77	94	86	81	77	84	80	76	82	78	75	80	77	74	73				73
5	90	82	75	71	89	81	75	70	79	74	70	77	73	69	75	72	69	67				67
6	86	76	70	65	84	75	69	65	74	68	64	72	68	64	71	67	64	62				62
7	81	71	65	60	80	70	64	60	69	64	60	68	63	59	67	62	59	58				58
8	77	67	60	56	75	66	60	56	65	59	56	64	59	55	63	58	55	54				54
9	73	63	56	52	72	62	56	52	61	56	52	60	55	52	59	55	52	50				50
10	69	59	53	49	68	59	53	49	58	52	49	57	52	48	56	52	48	47				47

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	75371
5°	74277
10°	71169
15°	67218
20°	62754
25°	56960
30°	47565
35°	34450
40°	21554
45°	12336
50°	6422
55°	3598
60°	2285
65°	1366
70°	970
75°	475
80°	707
85°	0



TEST NUMBER: P843246

CATALOG NUMBER: LD4C08DE010B35 EU4C08B35 4LBMH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	56.5	9.1
10°-20°	148.1	23.9
20°-30°	190.3	30.8
30°-40°	143.2	23.1
40°-50°	57.5	9.3
50°-60°	16.4	2.6
60°-70°	5.2	0.8
70°-80°	1.5	0.2
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	394.9	63.8
0°-40°	538.1	87.0
0°-60°	611.9	98.9
0°-90°	618.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	618.8	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	614	
5°	602	56
15°	528	148
25°	420	190
35°	230	143
45°	71	57
55°	17	16
65°	5	5
75°	1	2
85°	0	0
90°	0	



TEST NUMBER: P843246

CATALOG NUMBER: LD4C08DE010B35 EU4C08B35 4LBMH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	613.5
2.5°	609.7
5°	602.3
7.5°	588.3
10°	570.5
12.5°	549.1
15°	528.5
17.5°	505.1
20°	480.0
22.5°	452.9
25°	420.2
27.5°	381.0
30°	335.3
32.5°	283.9
35°	229.7
37.5°	179.3
40°	134.4
42.5°	99.0
45°	71.0
47.5°	48.5
50°	33.6
52.5°	23.4
55°	16.8
57.5°	12.2
60°	9.3
62.5°	6.6
65°	4.7
67.5°	3.7
70°	2.7
72.5°	1.9
75°	1.0
77.5°	1.0
80°	1.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)