

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P843252

Luminaire Tested: **LD4C08DE010B35 EU4C08B35 4LBWH**

Issue Date: 2/17/2023

**Test Information**

Test Method: LM-79-08  
Report Number: P843252  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P206636)  
Test Lab: INNOVATION CENTER  
Issue Date: 2/17/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD4C08DE010B35 EU4C08B35 4LBWH  
Description: 4in Downlight with BioUp LEDs  
Light Source: -  
Ballast/Driver:

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 688.5 lumens  
Efficiency: N/A  
Efficacy: 71.7 lumens/watt  
Spacing Criteria (0/90/45): 1.17 / 1.17 / 1.13  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct

Input Watts (W): 9.6  
Input Voltage (V):  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P843252

CATALOG NUMBER: LD4C08DE010B35 EU4C08B35 4LBWH

### Luminous Intensity Polar Plot





TEST NUMBER: P843252

CATALOG NUMBER: LD4C08DE010B35 EU4C08B35 4LBWH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91			
2	105	100	95	91	103	98	93	90	95	91	88	91	88	86	89	86	84	82			
3	99	91	85	80	97	90	84	80	87	82	78	84	80	77	82	79	76	74			
4	92	83	77	72	90	82	76	71	80	75	70	78	73	70	76	72	69	67			
5	87	77	70	65	85	76	69	64	74	68	64	72	67	63	70	66	62	61			
6	81	71	64	58	80	70	63	58	68	62	58	67	61	57	65	61	57	55			
7	76	65	58	53	75	65	58	53	63	57	53	62	56	52	61	56	52	50			
8	72	60	53	49	70	60	53	49	59	53	48	58	52	48	57	52	48	46			
9	67	56	49	45	66	56	49	45	55	49	44	54	48	44	53	48	44	43			
10	64	52	46	41	63	52	46	41	51	45	41	50	45	41	49	44	41	39			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	54522
5°	54731
10°	54902
15°	54894
20°	54596
25°	53313
30°	49821
35°	43163
40°	33727
45°	24185
50°	15711
55°	9403
60°	5504
65°	3546
70°	2371
75°	1756
80°	1344
85°	0



TEST NUMBER: P843252

CATALOG NUMBER: LD4C08DE010B35 EU4C08B35 4LBWH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	42.3	6.1
10°-20°	121.8	17.7
20°-30°	179.7	26.1
30°-40°	177.3	25.8
40°-50°	108.5	15.8
50°-60°	41.6	6.0
60°-70°	13.0	1.9
70°-80°	3.8	0.6
80°-90°	0.5	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	343.7	49.9
0°-40°	521.0	75.7
0°-60°	671.2	97.5
0°-90°	688.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	688.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	444	
5°	444	42
15°	432	122
25°	393	180
35°	288	177
45°	139	109
55°	44	42
65°	12	13
75°	4	4
85°	0	1
90°	0	



TEST NUMBER: P843252

CATALOG NUMBER: LD4C08DE010B35 EU4C08B35 4LBWH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	443.8
2.5°	444.7
5°	443.8
7.5°	442.8
10°	440.1
12.5°	436.3
15°	431.6
17.5°	426.0
20°	417.6
22.5°	408.2
25°	393.3
27.5°	374.6
30°	351.2
32.5°	322.4
35°	287.8
37.5°	249.4
40°	210.3
42.5°	173.8
45°	139.2
47.5°	108.4
50°	82.2
52.5°	60.7
55°	43.9
57.5°	30.8
60°	22.4
62.5°	16.8
65°	12.2
67.5°	9.3
70°	6.6
72.5°	4.7
75°	3.7
77.5°	1.9
80°	1.9
82.5°	1.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)