

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P843276

Luminaire Tested: **LD4C08DE010B50 EU4C08B50 4LBNH**

Issue Date: 2/17/2023



Test Information

Test Method: LM-79-08
Report Number: P843276
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207666)
Test Lab: INNOVATION CENTER
Issue Date: 2/17/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C08DE010B50 EU4C08B50 4LBNH
Description: 4in Downlight with BioUp LEDs
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 544.7 lumens
Efficiency: N/A
Efficacy: 56.7 lumens/watt
Spacing Criteria (0/90/45): 0.81 / 0.81 / 0.85
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 9.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P843276

CATALOG NUMBER: LD4C08DE010B50 EU4C08B50 4LBNH

Luminous Intensity Polar Plot





TEST NUMBER: P843276

CATALOG NUMBER: LD4C08DE010B50 EU4C08B50 4LBNH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	93			
2	108	103	99	96	106	101	98	94	98	95	92	95	93	90	92	90	89	87			
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81			
4	97	90	84	80	95	89	83	79	86	82	78	84	81	78	83	79	77	75			
5	92	84	78	74	91	83	78	73	81	76	73	80	75	72	78	74	72	70			
6	88	79	73	69	86	78	72	68	76	72	68	75	71	67	74	70	67	65			
7	83	74	68	64	82	73	68	64	72	67	63	71	66	63	70	66	63	61			
8	79	70	64	60	78	69	64	60	68	63	59	67	63	59	66	62	59	58			
9	76	66	60	56	74	65	60	56	65	59	56	64	59	56	63	59	55	54			
10	72	62	57	53	71	62	56	53	61	56	53	60	56	52	60	55	52	51			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	84019
5°	82145
10°	75959
15°	68147
20°	59996
25°	51632
30°	41579
35°	27686
40°	14402
45°	6515
50°	2829
55°	1906
60°	1229
65°	872
70°	718
75°	475
80°	0
85°	0



TEST NUMBER: P843276

CATALOG NUMBER: LD4C08DE010B50 EU4C08B50 4LBNH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	61.7	11.3
10°-20°	149.7	27.5
20°-30°	173.8	31.9
30°-40°	115.1	21.1
40°-50°	32.3	5.9
50°-60°	8.1	1.5
60°-70°	3.1	0.6
70°-80°	1.1	0.2
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	385.1	70.7
0°-40°	500.2	91.8
0°-60°	540.6	99.2
0°-90°	544.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	544.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	684	
5°	666	62
15°	536	150
25°	381	174
35°	185	115
45°	38	32
55°	9	8
65°	3	3
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P843276

CATALOG NUMBER: LD4C08DE010B50 EU4C08B50 4LBNH

CANDELA DISTRIBUTION (FULL):

	0°
0°	683.9
2.5°	680.9
5°	666.1
7.5°	640.4
10°	608.9
12.5°	573.3
15°	535.8
17.5°	499.3
20°	458.9
22.5°	421.4
25°	380.9
27.5°	342.5
30°	293.1
32.5°	240.8
35°	184.6
37.5°	132.2
40°	89.8
42.5°	58.2
45°	37.5
47.5°	22.7
50°	14.8
52.5°	10.8
55°	8.9
57.5°	6.9
60°	5.0
62.5°	3.9
65°	3.0
67.5°	2.0
70°	2.0
72.5°	1.0
75°	1.0
77.5°	1.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)