

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P758773

Luminaire Tested: LD6D05D010-EU6DR700210IC9027-6LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P758773
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D05D010-EU6DR700210IC9027-6LBDP1B
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 375.9 lumens
Efficiency: N/A
Efficacy: 50.1 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 7.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P758773

CATALOG NUMBER: LD6D05D010-EU6DR700210IC9027-6LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P758773

CATALOG NUMBER: LD6D05D010-EU6DR700210IC9027-6LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	46174
5°	44804
10°	43546
15°	42984
20°	40126
25°	30151
30°	21322
35°	7549
40°	3965
45°	4234
50°	4385
55°	4457
60°	4480
65°	4395
70°	4153
75°	3842
80°	3398
85°	2758

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 4494 cd/sqm



TEST NUMBER: P758773

CATALOG NUMBER: LD6D05D010-EU6DR700210IC9027-6LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	38.5	10.2
10°-20°	105.7	28.1
20°-30°	116.4	31.0
30°-40°	44.5	11.8
40°-50°	21.0	5.6
50°-60°	20.9	5.6
60°-70°	16.7	4.4
70°-80°	9.6	2.6
80°-90°	2.6	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	260.6	69.3
0°-40°	305.1	81.2
0°-60°	346.9	92.3
0°-90°	375.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	375.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	423	
5°	408	39
15°	380	106
25°	250	116
35°	57	44
45°	27	21
55°	23	21
65°	17	17
75°	9	10
85°	2	3
90°	0	



TEST NUMBER: P758773

CATALOG NUMBER: LD6D05D010-EU6DR700210IC9027-6LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	422.6
2.5°	418.1
5°	408.5
7.5°	400.4
10°	392.5
12.5°	385.9
15°	380.0
17.5°	365.6
20°	345.1
22.5°	301.1
25°	250.1
27.5°	217.7
30°	169.0
32.5°	109.1
35°	56.6
37.5°	30.6
40°	27.8
42.5°	27.6
45°	27.4
47.5°	26.8
50°	25.8
52.5°	24.6
55°	23.4
57.5°	22.1
60°	20.5
62.5°	18.8
65°	17.0
67.5°	15.0
70°	13.0
72.5°	11.0
75°	9.1
77.5°	7.2
80°	5.4
82.5°	3.8
85°	2.2
87.5°	0.9
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)