

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P758826

Luminaire Tested: LD6D05D010-EU6DR700210IC9050-6LBDP1H

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P758826
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D05D010-EU6DR700210IC9050-6LBDP1H
Description: 6 INCH ROUND DEEP 45° CUTOFF SEMI-SPECULAR CLEAR TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 715.2 lumens
Efficiency: N/A
Efficacy: 95.4 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 7.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P758826

CATALOG NUMBER: LD6D05D010-EU6DR700210IC9050-6LBDP1H

Luminous Intensity Polar Plot





TEST NUMBER: P758826

CATALOG NUMBER: LD6D05D010-EU6DR700210IC9050-6LBDP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	87846
5°	85242
10°	82855
15°	81771
20°	76356
25°	57360
30°	40549
35°	14365
40°	7545
45°	8050
50°	8329
55°	8496
60°	8544
65°	8351
70°	7891
75°	7303
80°	6481
85°	5265

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 60°
 Luminance: 8544 cd/sqm



TEST NUMBER: P758826

CATALOG NUMBER: LD6D05D010-EU6DR700210IC9050-6LBDP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	73.3	10.2
10°-20°	201.1	28.1
20°-30°	221.4	31.0
30°-40°	84.6	11.8
40°-50°	40.0	5.6
50°-60°	39.7	5.6
60°-70°	31.8	4.4
70°-80°	18.3	2.6
80°-90°	5.0	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	495.8	69.3
0°-40°	580.4	81.2
0°-60°	660.1	92.3
0°-90°	715.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	715.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	804	
5°	777	73
15°	723	201
25°	476	221
35°	108	85
45°	52	40
55°	45	40
65°	32	32
75°	17	18
85°	4	5
90°	0	



TEST NUMBER: P758826

CATALOG NUMBER: LD6D05D010-EU6DR700210IC9050-6LBDP1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	804.0
2.5°	795.6
5°	777.2
7.5°	761.7
10°	746.8
12.5°	734.2
15°	722.9
17.5°	695.6
20°	656.7
22.5°	573.0
25°	475.8
27.5°	414.2
30°	321.4
32.5°	207.6
35°	107.7
37.5°	58.2
40°	52.9
42.5°	52.6
45°	52.1
47.5°	50.9
50°	49.0
52.5°	46.9
55°	44.6
57.5°	42.0
60°	39.1
62.5°	35.8
65°	32.3
67.5°	28.5
70°	24.7
72.5°	20.9
75°	17.3
77.5°	13.6
80°	10.3
82.5°	7.3
85°	4.2
87.5°	1.7
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)