

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P768628

Luminaire Tested: LD6D55D010-EU6DR7055659050-6LBS1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P768628
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-76)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D55D010-EU6DR7055659050-6LBS1MW
Description: 6 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6998.7 lumens
Efficiency: N/A
Efficacy: 120.3 lumens/watt
Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.04
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 58.2
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P768628
CATALOG NUMBER: LD6D55D010-EU6DR7055659050-6LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P768628
 CATALOG NUMBER: LD6D55D010-EU6DR7055659050-6LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100	
1	113	110	107	105	111	108	106	103	104	102	100	100	99	97	97	95	94	93			93	
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85			85	
3	101	94	88	84	99	92	87	83	90	85	82	87	84	81	85	82	79	78			78	
4	95	87	81	76	93	86	80	76	83	78	75	81	77	74	79	76	73	71			71	
5	89	80	74	69	88	79	73	69	78	72	68	76	71	68	74	70	67	65			65	
6	84	75	68	63	83	74	68	63	72	67	63	71	66	62	69	65	62	60			60	
7	80	69	63	58	78	69	62	58	67	62	58	66	61	57	65	61	57	56			56	
8	75	65	58	54	74	64	58	54	63	57	53	62	57	53	61	56	53	51			51	
9	71	61	54	50	70	60	54	50	59	53	50	58	53	49	57	53	49	48			48	
10	67	57	50	46	66	56	50	46	55	50	46	55	50	46	54	49	46	44			44	

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	603545
5°	602045
10°	600741
15°	600573
20°	594701
25°	558644
30°	498030
35°	397080
40°	263665
45°	157639
50°	81726
55°	42956
60°	15187
65°	259
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 157639 cd/sqm



TEST NUMBER: P768628

CATALOG NUMBER: LD6D55D010-EU6DR7055659050-6LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	522.0	7.5
10°-20°	1497.2	21.4
20°-30°	2112.1	30.2
30°-40°	1823.3	26.1
40°-50°	816.5	11.7
50°-60°	213.8	3.1
60°-70°	13.9	0.2
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4131.2	59.0
0°-40°	5954.5	85.1
0°-60°	6984.8	99.8
0°-90°	6998.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6998.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5524	
5°	5489	522
15°	5309	1497
25°	4634	2112
35°	2977	1823
45°	1020	817
55°	226	214
65°	1	14
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P768628

CATALOG NUMBER: LD6D55D010-EU6DR7055659050-6LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	5523.9
2.5°	5518.0
5°	5489.2
7.5°	5465.3
10°	5414.7
12.5°	5369.0
15°	5309.4
17.5°	5240.8
20°	5114.7
22.5°	4907.1
25°	4633.9
27.5°	4317.0
30°	3947.5
32.5°	3495.6
35°	2977.0
37.5°	2404.9
40°	1848.6
42.5°	1404.6
45°	1020.2
47.5°	703.3
50°	480.8
52.5°	331.8
55°	225.5
57.5°	136.1
60°	69.5
62.5°	21.9
65°	1.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)