

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P769182

Luminaire Tested: LD6D60D010-EU6DR6055659024-6LBDP1LI

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P769182
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D60D010-EU6DR6055659024-6LBDP1LI
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6460.3 lumens
Efficiency: N/A
Efficacy: 100.3 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 64.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P769182
CATALOG NUMBER: LD6D60D010-EU6DR6055659024-6LBDP1LI

Luminous Intensity Polar Plot





TEST NUMBER: P769182
 CATALOG NUMBER: LD6D60D010-EU6DR6055659024-6LBDP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	838292
5°	858900
10°	869275
15°	828104
20°	730135
25°	590555
30°	399459
35°	200167
40°	32477
45°	31784
50°	32415
55°	32898
60°	33827
65°	34592
70°	35396
75°	35841
80°	34543
85°	28833

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 35841 cd/sqm



TEST NUMBER: P769182

CATALOG NUMBER: LD6D60D010-EU6DR6055659024-6LBDP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	748.5	11.6
10°-20°	2025.0	31.3
20°-30°	2178.7	33.7
30°-40°	947.0	14.7
40°-50°	159.1	2.5
50°-60°	154.7	2.4
60°-70°	132.3	2.0
70°-80°	88.5	1.4
80°-90°	26.5	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4952.2	76.7
0°-40°	5899.3	91.3
0°-60°	6213.0	96.2
0°-90°	6460.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6460.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7672	
5°	7831	748
15°	7321	2025
25°	4899	2179
35°	1501	947
45°	206	159
55°	173	155
65°	134	132
75°	85	89
85°	23	26
90°	0	



TEST NUMBER: P769182

CATALOG NUMBER: LD6D60D010-EU6DR6055659024-6LBDP1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	7672.4
2.5°	7888.0
5°	7831.1
7.5°	7849.1
10°	7835.1
12.5°	7673.4
15°	7320.9
17.5°	6847.6
20°	6279.5
22.5°	5671.4
25°	4898.6
27.5°	3918.1
30°	3166.2
32.5°	2440.3
35°	1500.7
37.5°	642.0
40°	227.7
42.5°	209.7
45°	205.7
47.5°	198.7
50°	190.7
52.5°	181.7
55°	172.7
57.5°	163.8
60°	154.8
62.5°	144.8
65°	133.8
67.5°	122.8
70°	110.8
72.5°	97.9
75°	84.9
77.5°	69.9
80°	54.9
82.5°	38.9
85°	23.0
87.5°	8.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)