

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P769375

Luminaire Tested: LD6D60D010-EU6DR7055659035-6LBDP1B

Issue Date: 2/5/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P769375  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/5/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD6D60D010-EU6DR7055659035-6LBDP1B  
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 4249.2 lumens  
Efficiency: N/A  
Efficacy: 66.0 lumens/watt  
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct

Input Watts (W): 64.4  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT




Downlight

TEST NUMBER: P769375

CATALOG NUMBER: LD6D60D010-EU6DR7055659035-6LBDP1B

### Luminous Intensity Polar Plot





TEST NUMBER: P769375

CATALOG NUMBER: LD6D60D010-EU6DR7055659035-6LBDP1B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	521982
5°	506472
10°	492357
15°	485897
20°	453732
25°	340860
30°	240960
35°	85352
40°	44886
45°	47808
50°	49498
55°	50423
60°	50741
65°	49664
70°	46864
75°	43439
80°	38570
85°	31341

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 57.5°  
 Luminance: 50757 cd/sqm



TEST NUMBER: P769375

CATALOG NUMBER: LD6D60D010-EU6DR7055659035-6LBDP1B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	435.6	10.3
10°-20°	1194.7	28.1
20°-30°	1315.8	31.0
30°-40°	502.7	11.8
40°-50°	237.4	5.6
50°-60°	236.0	5.6
60°-70°	188.9	4.4
70°-80°	108.6	2.6
80°-90°	29.5	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2946.1	69.3
0°-40°	3448.8	81.2
0°-60°	3922.2	92.3
0°-90°	4249.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4249.2	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4777	
5°	4618	436
15°	4296	1195
25°	2827	1316
35°	640	503
45°	309	237
55°	265	236
65°	192	189
75°	103	109
85°	25	30
90°	0	



TEST NUMBER: P769375

CATALOG NUMBER: LD6D60D010-EU6DR7055659035-6LBDP1B

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	4777.4
2.5°	4727.5
5°	4617.8
7.5°	4526.3
10°	4437.8
12.5°	4362.9
15°	4295.6
17.5°	4133.0
20°	3902.3
22.5°	3404.5
25°	2827.4
27.5°	2461.3
30°	1909.9
32.5°	1233.7
35°	639.9
37.5°	345.7
40°	314.7
42.5°	312.4
45°	309.4
47.5°	302.6
50°	291.2
52.5°	278.4
55°	264.7
57.5°	249.6
60°	232.2
62.5°	212.5
65°	192.1
67.5°	169.4
70°	146.7
72.5°	124.0
75°	102.9
77.5°	80.9
80°	61.3
82.5°	43.1
85°	25.0
87.5°	9.8
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)