

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P769408

Luminaire Tested: LD6D60D010-EU6DR7055659050-6LBS1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P769408
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-76)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D60D010-EU6DR7055659050-6LBS1MW
Description: 6 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7696.0 lumens
Efficiency: N/A
Efficacy: 119.5 lumens/watt
Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.04
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 64.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P769408
CATALOG NUMBER: LD6D60D010-EU6DR7055659050-6LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P769408

CATALOG NUMBER: LD6D60D010-EU6DR7055659050-6LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0													
RCR	0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	99	97	97	95	94	93											
	1	113	110	107	105	111	108	106	103	104	102	100	100	99	97	97	95	94	93	93	92	90	94	91	88	85											
	2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85	85	82	79	85	82	79	78											
	3	101	94	88	84	99	92	87	83	90	85	82	87	84	81	85	82	79	78	78	75	74	79	76	73	71											
	4	95	87	81	76	93	86	80	76	83	78	75	81	77	74	79	76	73	71	71	68	67	74	70	67	65											
	5	89	80	74	69	88	79	73	69	78	72	68	76	71	68	74	70	67	65	65	62	62	69	65	62	60											
	6	84	75	68	63	83	74	68	63	72	67	63	71	66	62	69	65	62	60	60	57	57	65	61	57	56											
	7	80	69	63	58	78	69	62	58	67	62	58	66	61	57	65	61	57	56	56	53	53	61	56	53	51											
	8	75	65	58	54	74	64	58	54	63	57	53	62	57	53	61	56	53	51	51	49	49	57	53	49	48											
	9	71	61	54	50	70	60	54	50	59	53	50	58	53	49	57	53	49	48	48	46	46	54	49	46	44											
	10	67	57	50	46	66	56	50	46	55	50	46	55	50	46	54	49	46	44	44	42	42	50	45	42	40											

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	663694
5°	662028
10°	660596
15°	660411
20°	653953
25°	614305
30°	547663
35°	436655
40°	289938
45°	173338
50°	89868
55°	47242
60°	16717
65°	284
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 173338 cd/sqm



TEST NUMBER: P769408

CATALOG NUMBER: LD6D60D010-EU6DR7055659050-6LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	574.0	7.5
10°-20°	1646.3	21.4
20°-30°	2322.5	30.2
30°-40°	2004.9	26.1
40°-50°	897.9	11.7
50°-60°	235.1	3.1
60°-70°	15.3	0.2
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4542.9	59.0
0°-40°	6547.8	85.1
0°-60°	7680.7	99.8
0°-90°	7696.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7696.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6074	
5°	6036	574
15°	5838	1646
25°	5096	2322
35°	3274	2005
45°	1122	898
55°	248	235
65°	1	15
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P769408
CATALOG NUMBER: LD6D60D010-EU6DR7055659050-6LBS1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	6074.4
2.5°	6067.8
5°	6036.1
7.5°	6009.9
10°	5954.2
12.5°	5904.0
15°	5838.4
17.5°	5763.1
20°	5624.3
22.5°	5396.0
25°	5095.6
27.5°	4747.2
30°	4340.9
32.5°	3843.9
35°	3273.7
37.5°	2644.5
40°	2032.8
42.5°	1544.5
45°	1121.8
47.5°	773.4
50°	528.7
52.5°	364.8
55°	248.0
57.5°	149.6
60°	76.5
62.5°	24.0
65°	1.1
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)