

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P770077

Luminaire Tested: LD6D65D010-EU6DR6555659035-6LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P770077
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D65D010-EU6DR6555659035-6LBDP1B
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5223.1 lumens
Efficiency: N/A
Efficacy: 71.7 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 72.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P770077
CATALOG NUMBER: LD6D65D010-EU6DR6555659035-6LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P770077

CATALOG NUMBER: LD6D65D010-EU6DR6555659035-6LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93																			
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87																			
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80																			
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69																			
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65																			
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60																			
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57																			
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53																			
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	561873
5°	562331
10°	582135
15°	583097
20°	536832
25°	457413
30°	350167
35°	247385
40°	146024
45°	59289
50°	21485
55°	11963
60°	6862
65°	3775
70°	3961
75°	3082
80°	3209
85°	2758

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 59289 cd/sqm



TEST NUMBER: P770077

CATALOG NUMBER: LD6D65D010-EU6DR6555659035-6LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	495.2	9.5
10°-20°	1428.4	27.3
20°-30°	1713.8	32.8
30°-40°	1151.7	22.0
40°-50°	344.8	6.6
50°-60°	60.8	1.2
60°-70°	17.3	0.3
70°-80°	8.5	0.2
80°-90°	2.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3637.3	69.6
0°-40°	4789.0	91.7
0°-60°	5194.6	99.5
0°-90°	5223.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5223.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5142	
5°	5127	495
15°	5155	1428
25°	3794	1714
35°	1855	1152
45°	384	345
55°	63	61
65°	15	17
75°	7	8
85°	2	3
90°	0	



TEST NUMBER: P770077

CATALOG NUMBER: LD6D65D010-EU6DR6555659035-6LBDP1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	5142.5
2.5°	5164.4
5°	5127.1
7.5°	5204.6
10°	5247.0
12.5°	5236.7
15°	5154.9
17.5°	4954.7
20°	4617.0
22.5°	4219.5
25°	3794.2
27.5°	3314.1
30°	2775.5
32.5°	2287.3
35°	1854.7
37.5°	1427.2
40°	1023.8
42.5°	668.7
45°	383.7
47.5°	203.2
50°	126.4
52.5°	87.7
55°	62.8
57.5°	45.3
60°	31.4
62.5°	20.5
65°	14.6
67.5°	13.2
70°	12.4
72.5°	9.5
75°	7.3
77.5°	6.6
80°	5.1
82.5°	3.7
85°	2.2
87.5°	1.5
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)