

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P770355

Luminaire Tested: LD6D70BD010-EU6DR3570959024-6LBS1H

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P770355
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-20)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D70BD010-EU6DR3570959024-6LBS1H
Description: 6 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 35° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6954.1 lumens
Efficiency: N/A
Efficacy: 104.4 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.54
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 66.6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P770355
CATALOG NUMBER: LD6D70BD010-EU6DR3570959024-6LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P770355

CATALOG NUMBER: LD6D70BD010-EU6DR3570959024-6LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0													
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100														
1	115	112	110	108	112	110	108	107	106	105	103	103	101	100	99	98	98	96					96														
2	110	106	103	101	108	105	102	99	102	99	97	99	97	95	96	95	93	92					92														
3	106	101	97	94	105	100	96	93	97	95	92	95	93	91	93	91	89	88					88														
4	103	97	92	89	101	96	92	89	94	90	88	92	89	87	90	88	86	84					84														
5	99	93	88	85	98	92	87	84	90	86	84	89	85	83	87	84	82	81					81														
6	96	89	84	81	94	88	84	81	87	83	80	85	82	80	84	81	79	78					78														
7	93	85	81	78	91	85	80	77	84	80	77	83	79	77	82	79	76	75					75														
8	90	82	78	74	88	82	77	74	81	77	74	80	76	74	79	76	73	72					72														
9	87	79	75	72	86	79	75	72	78	74	71	77	74	71	77	73	71	70					70														
10	84	77	72	69	83	76	72	69	76	72	69	75	71	69	74	71	69	68					68														

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2090617
5°	2041494
10°	1839922
15°	1428078
20°	809980
25°	315121
30°	117559
35°	64437
40°	42119
45°	25635
50°	16318
55°	11525
60°	8435
65°	4576
70°	319
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 25635 cd/sqm



TEST NUMBER: P770355

CATALOG NUMBER: LD6D70BD010-EU6DR3570959024-6LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1711.9	24.6
10°-20°	3342.4	48.1
20°-30°	1363.1	19.6
30°-40°	326.2	4.7
40°-50°	136.0	2.0
50°-60°	56.3	0.8
60°-70°	17.6	0.3
70°-80°	0.4	0.0
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6417.4	92.3
0°-40°	6743.6	97.0
0°-60°	6935.8	99.7
0°-90°	6954.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6954.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	19134	
5°	18614	###
15°	12625	3342
25°	2614	1363
35°	483	326
45°	166	136
55°	60	56
65°	18	18
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P770355

CATALOG NUMBER: LD6D70BD010-EU6DR3570959024-6LBS1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	19134.2
2.5°	19019.4
5°	18613.5
7.5°	17803.8
10°	16583.9
12.5°	14866.4
15°	12625.0
17.5°	9883.8
20°	6966.2
22.5°	4442.1
25°	2613.9
27.5°	1477.6
30°	931.8
32.5°	654.3
35°	483.1
37.5°	373.6
40°	295.3
42.5°	227.5
45°	165.9
47.5°	124.2
50°	96.0
52.5°	76.2
55°	60.5
57.5°	49.0
60°	38.6
62.5°	28.2
65°	17.7
67.5°	6.3
70°	1.0
72.5°	1.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	1.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)