

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P770224

Luminaire Tested: LD6D70BD010-EU6DR2570959030-6LBS1B

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P770224
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-4)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D70BD010-EU6DR2570959030-6LBS1B
Description: 6 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 25° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7107.4 lumens
Efficiency: N/A
Efficacy: 106.7 lumens/watt
Spacing Criteria (0/90/45): 0.42 / 0.42 / 0.45
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 66.6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P770224

CATALOG NUMBER: LD6D70BD010-EU6DR2570959030-6LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P770224

CATALOG NUMBER: LD6D70BD010-EU6DR2570959030-6LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20								
RC	80									50									30									10									0								
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0															
RCR	0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																										
	1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96																										
	2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92																										
	3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89																										
	4	103	97	93	90	102	96	93	90	94	91	89	93	90	88	91	89	87	85																										
	5	100	93	89	86	98	93	89	86	91	87	85	89	86	84	88	85	83	82																										
	6	97	90	85	82	95	89	85	82	88	84	81	87	83	81	85	83	80	79																										
	7	93	87	82	79	92	86	82	79	85	81	78	84	80	78	83	80	78	77																										
	8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74																										
	9	88	81	76	73	87	80	76	73	80	76	73	79	75	73	78	75	73	72																										
	10	85	78	74	71	85	78	74	71	77	73	71	76	73	71	76	73	70	69																										

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2945298
5°	2743170
10°	1956782
15°	1152473
20°	717078
25°	393531
30°	179972
35°	68159
40°	30865
45°	18558
50°	7700
55°	4972
60°	3474
65°	2353
70°	351
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 18558 cd/sqm



TEST NUMBER: P770224

CATALOG NUMBER: LD6D70BD010-EU6DR2570959030-6LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2149.5	30.2
10°-20°	2911.4	41.0
20°-30°	1540.6	21.7
30°-40°	380.3	5.4
40°-50°	92.8	1.3
50°-60°	24.4	0.3
60°-70°	8.2	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6601.5	92.9
0°-40°	6981.8	98.2
0°-60°	7099.0	99.9
0°-90°	7107.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7107.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	26957	
5°	25011	###
15°	10188	2911
25°	3264	1541
35°	511	380
45°	120	93
55°	26	24
65°	9	8
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P770224

CATALOG NUMBER: LD6D70BD010-EU6DR2570959030-6LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	26956.6
2.5°	26513.6
5°	25011.1
7.5°	21992.7
10°	17637.2
12.5°	13332.7
15°	10188.5
17.5°	7940.5
20°	6167.2
22.5°	4625.1
25°	3264.3
27.5°	2189.1
30°	1426.5
32.5°	867.9
35°	511.0
37.5°	312.7
40°	216.4
42.5°	165.4
45°	120.1
47.5°	72.5
50°	45.3
52.5°	32.9
55°	26.1
57.5°	20.4
60°	15.9
62.5°	12.5
65°	9.1
67.5°	3.4
70°	1.1
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)