

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P770861

Luminaire Tested: LD6D70BD010-EU6DR6570959035-6LBS1B

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P770861
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D70BD010-EU6DR6570959035-6LBS1B
Description: 6 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6985.3 lumens
Efficiency: N/A
Efficacy: 104.9 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct


Input Watts (W): 66.6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P770861
CATALOG NUMBER: LD6D70BD010-EU6DR6570959035-6LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P770861

CATALOG NUMBER: LD6D70BD010-EU6DR6570959035-6LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	93			93
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85			85
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78			78
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72			72
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66			66
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62	61			61
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56			56
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52			52
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50	49			49
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47	46			46

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	370421
5°	369491
10°	369173
15°	357790
20°	325727
25°	283852
30°	236084
35°	187064
40°	135015
45°	85296
50°	44458
55°	23633
60°	12417
65°	6827
70°	2869
75°	3159
80°	2186
85°	1876

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 85296 cd/sqm



TEST NUMBER: P770861

CATALOG NUMBER: LD6D70BD010-EU6DR6570959035-6LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	599.8	8.6
10°-20°	1642.5	23.5
20°-30°	2007.7	28.7
30°-40°	1629.0	23.3
40°-50°	811.7	11.6
50°-60°	226.4	3.2
60°-70°	51.5	0.7
70°-80°	13.4	0.2
80°-90°	3.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4249.9	60.8
0°-40°	5878.9	84.2
0°-60°	6917.0	99.0
0°-90°	6985.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6985.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6342	
5°	6302	600
15°	5917	1642
25°	4405	2008
35°	2624	1629
45°	1033	812
55°	232	226
65°	49	51
75°	14	13
85°	3	3
90°	0	



TEST NUMBER: P770861

CATALOG NUMBER: LD6D70BD010-EU6DR6570959035-6LBS1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	6342.4
2.5°	6337.8
5°	6302.4
7.5°	6281.9
10°	6225.0
12.5°	6109.4
15°	5917.4
17.5°	5617.3
20°	5240.8
22.5°	4834.4
25°	4404.8
27.5°	3945.3
30°	3500.7
32.5°	3061.7
35°	2623.7
37.5°	2186.5
40°	1770.9
42.5°	1381.3
45°	1032.7
47.5°	719.5
50°	489.3
52.5°	337.4
55°	232.1
57.5°	156.6
60°	106.3
62.5°	73.6
65°	49.4
67.5°	25.2
70°	16.8
72.5°	15.8
75°	14.0
77.5°	9.3
80°	6.5
82.5°	4.7
85°	2.8
87.5°	1.9
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)