

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P770889

Luminaire Tested: LD6D70BD010-EU6DR6570959050-6LBS1LI

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P770889
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D70BD010-EU6DR6570959050-6LBS1LI
Description: 6 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8328.1 lumens
Efficiency: N/A
Efficacy: 125.0 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 66.6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P770889

CATALOG NUMBER: LD6D70BD010-EU6DR6570959050-6LBS1LI

Luminous Intensity Polar Plot





TEST NUMBER: P770889

CATALOG NUMBER: LD6D70BD010-EU6DR6570959050-6LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10		0		
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	93			
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85			
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78			
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72			
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66			
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62	61			
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56			
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52			
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50	49			
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47	46			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	441627
5°	440517
10°	440137
15°	426568
20°	388339
25°	338415
30°	281463
35°	223020
40°	160967
45°	101692
50°	53008
55°	28175
60°	14800
65°	8140
70°	3415
75°	3768
80°	2623
85°	2211

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 101692 cd/sqm



TEST NUMBER: P770889

CATALOG NUMBER: LD6D70BD010-EU6DR6570959050-6LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	715.1	8.6
10°-20°	1958.2	23.5
20°-30°	2393.6	28.7
30°-40°	1942.1	23.3
40°-50°	967.8	11.6
50°-60°	270.0	3.2
60°-70°	61.4	0.7
70°-80°	16.0	0.2
80°-90°	4.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5066.9	60.8
0°-40°	7009.0	84.2
0°-60°	8246.7	99.0
0°-90°	8328.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	8328.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7562	
5°	7514	715
15°	7055	1958
25°	5252	2394
35°	3128	1942
45°	1231	968
55°	277	270
65°	59	61
75°	17	16
85°	3	4
90°	0	



TEST NUMBER: P770889

CATALOG NUMBER: LD6D70BD010-EU6DR6570959050-6LBS1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	7561.6
2.5°	7556.1
5°	7513.9
7.5°	7489.4
10°	7421.6
12.5°	7283.9
15°	7054.9
17.5°	6697.1
20°	6248.2
22.5°	5763.7
25°	5251.5
27.5°	4703.7
30°	4173.6
32.5°	3650.3
35°	3128.0
37.5°	2606.9
40°	2111.3
42.5°	1646.8
45°	1231.2
47.5°	857.8
50°	583.4
52.5°	402.3
55°	276.7
57.5°	186.7
60°	126.7
62.5°	87.8
65°	58.9
67.5°	30.0
70°	20.0
72.5°	18.9
75°	16.7
77.5°	11.1
80°	7.8
82.5°	5.6
85°	3.3
87.5°	2.2
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)